

PRODUCT DATASHEET

NEON FLEX 5M

NEON FLEX | Decorative warm white LED Strips for outdoor use with homogeneous illumination



TECHNICAL DATA

Electrical data


Nominal wattage	29.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	140 mA
Power factor λ	> 0.50
Protection class	II
Operating mode	External LED driver

Photometrical data

Luminous flux	1700 lm
Luminous efficacy	59 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdcm
Beam angle	110 °

Dimensions & Weight

Length	5000.00 mm
Width	13.50 mm
Height	6.70 mm
Product weight	700.00 g



Materials & Colors

Body material	Silicone
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Plug type C (EU)
Type of protection	IP44
Dimmable	No
Mounting type	Surface
Mounting location	All surfaces
LED module replaceable	Not replaceable




Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Certificates & Standards

Standards	CE / EAC / REACH / RoHS
-----------	-------------------------

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction NEON FLEX
	Tender documents Tender Text 4058075504721
	Declarations of conformity NEON FLEX 3M and 5M

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075504721	Folding box 1	64 mm x 299 mm x 275 mm	982.00 g	5.26 dm ³
4058075504738	Shipping box 4	570 mm x 314 mm x 158 mm	4433.00 g	28.28 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.