

# PRODUCT DATASHEET

## ENDURA STYLE EDGE Wall updown 7W

ENDURA STYLE EDGE | Stainless steel wall luminaire with light outlet up and down



## TECHNICAL DATA

### Electrical data


|                        |               |
|------------------------|---------------|
| Nominal wattage        | 7.00 W        |
| Nominal voltage        | 220...240 V   |
| Mains frequency        | 50...60 Hz    |
| Power factor $\lambda$ | > 0.5         |
| Protection class       | I             |
| Operating mode         | Mains voltage |

### Photometrical data

|                                      |            |
|--------------------------------------|------------|
| Luminous flux                        | 360 lm     |
| Luminous efficacy                    | 51 lm/W    |
| Color temperature                    | 3000 K     |
| Light color (designation)            | Warm White |
| Color rendering index Ra             | $\geq 80$  |
| Standard deviation of color matching | < 6 sdcn   |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 110.00 mm |
| Width          | 120.00 mm |
| Height         | 260.00 mm |
| Product weight | 870.00 g  |



### Materials & Colors

|               |                 |
|---------------|-----------------|
| Product color | Steel           |
| Housing color | Steel           |
| Body material | Stainless steel |

|                 |                    |
|-----------------|--------------------|
| Cover material  | Polycarbonate (PC) |
| Mercury content | 0.0 mg             |

### Application & Mounting

|                           |                             |
|---------------------------|-----------------------------|
| Ambient temperature range | -20...+40 °C                |
| Type of connection        | Terminal, 3-Pole (L, N, PE) |
| Type of protection        | IP44                        |
| Dimmable                  | No                          |
| Mounting type             | Surface                     |
| Mounting location         | Wall                        |
| LED module replaceable    | Not replaceable             |

### Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 25000 h |
| Number of switching cycles | 12500   |

### Certificates & Standards

|           |                         |
|-----------|-------------------------|
| Standards | CE / EAC / REACH / RoHS |
|-----------|-------------------------|

### DOWNLOAD DATA

| DOWNLOAD DATA                                                                       |                                                                 |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------|
|   | User instruction<br>ENDURA STYLE EDGE WALL UPDOWN               |
|  | Tender documents<br>Tender Text 4058075478091                   |
|   | Declarations of conformity<br>ENDURA STYLE EDGE WALLUPDOWN 7WST |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075478091 | Folding box<br>1             | 127 mm x 127 mm x 264 mm             | 956.00 g     | 4.26 dm <sup>3</sup>  |
| 4058075478107 | Shipping box<br>4            | 268 mm x 268 mm x 289 mm             | 4265.00 g    | 20.76 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.