

PRODUCT DATASHEET ORBIS SPARKLEDOT CLICK SENSOR 340 24W

ORBIS CLICK SENSOR | Luminaires activated by sensor mode or conventional wall switch



Areas of application

- Corridors, entrance areas

Product benefits

- Easy and quick installation

Product features

- Luminaires activated by sensor mode or conventional wall switch
- Operating mode easily changed by three clicks of wall switch
- Motion sensor (microwave technology) with adjustable detection parameters



TECHNICAL DATA

Electrical data


Nominal wattage	24.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor λ	> 0.70
Protection class	Ш
Operating mode	Mains voltage

Photometrical data

Luminous flux	1680 lm	
Luminous efficacy	70 lm/W	
Color temperature	3000 К	
Light color (designation)	Warm White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Beam angle	120 °	

Dimensions & Weight

Diameter	340.00 mm
Height	80.00 mm
Product weight	503.00 g



Materials & Colors

Product color	White
Housing color	White

Body material	Steel	
Cover material	Polymethylmethacrylate (PMMA)	
Mercury content	0.0 mg	

Application & Mounting

Ambient temperature range	-2040 °C
Type of connection	Push button terminal, 2-pole
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Sensor

Type of sensor	Light / Motion	
Sensor technology	Microwave	
Sensor controlled switching time	5 s30 min	
Detection range of motion sensor	26 m	
Detection threshold of daylight sensor	250 lx	

Certificates & Standards

ırds	CE / EAC / REACH / RoHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

DOWNLOAD DATA

	DOWNLOAD DATA
POF	User instruction ORBIS
1	Tender documents Tender Text 4058075472877

	DOWNLOAD DATA
POF	Declarations of conformity ORBIS CLICK SEN
PDF	Packaging insert Legal insert

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075472877	Folding box 1	367 mm x 92 mm x 367 mm	758.00 g	12.39 dm ³
4058075472884	Shipping box 5	482 mm x 382 mm x 390 mm	4843.00 g	71.81 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.