

# PRODUCT DATASHEET ORBIS SQUARE CLICK SENSOR 430 50W

ORBIS CLICK SENSOR | Luminaires activated by sensor mode or conventional wall switch



#### Areas of application

- Corridors, entrance areas

#### **Product benefits**

- Easy and quick installation

#### **Product features**

- Luminaires activated by sensor mode or conventional wall switch
- Operating mode easily changed by three clicks of wall switch
- Motion sensor (microwave technology) with adjustable detection parameters



# **TECHNICAL DATA**

# Electrical data


Nominal wattage	50.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor λ	> 0.70
Protection class	П
Operating mode	Mains voltage

# Photometrical data

Luminous flux	3700 lm
Luminous efficacy	74 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Beam angle	120 °

# **Dimensions & Weight**

Length	430.00 mm
Width	430.00 mm
Height	80.00 mm
Product weight	1395.00 g



# Materials & Colors

Product color	White
Housing color	White

Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-2040 °C
Type of connection	Push button terminal, 2-pole
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
LED module replaceable	Not replaceable

## Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

## Sensor

Type of sensor	Light / Motion
Sensor technology	Microwave
Sensor controlled switching time	5 s30 min
Detection range of motion sensor	26 m
Detection threshold of daylight sensor	250 lx

#### Certificates & Standards

Standards	CE / EAC / REACH / RoHS

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

## **DOWNLOAD DATA**

	DOWNLOAD DATA
PDF	User instruction ORBIS SQUARE
	Tender documents Tender Text 4058075472815

	DOWNLOAD DATA
PDF	Declarations of conformity ORBIS CLICK SEN
PDF	Packaging insert Legal insert

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075472815	Folding box 1	542 mm x 142 mm x 547 mm	1965.00 g	42.10 dm <sup>3</sup>
4058075472822	Shipping box 5	737 mm x 557 mm x 570 mm	12126.00 g	233.99 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.