




Spectrum Test Report

Sample : Date : 2024-10-23 19:34:41
Specification : CYLINDPS010UNHD8SC2R3BZP Min 500(Sam. Status) + up:
Sample No. : Standard : LM-79-19
Manufacturer : LEDVANCE LLC Instrument : HaasSuite(EVERFINE)
Remark : Test by : Alan Wang

Test Condition

Temperature : 25.3Deg RH : 65.0%
WL Range : 380nm-780nm IP : 50432 (77%)
Test Mode : Accuracy Test T : 4069 ms

Spectrum : Low



Colorimetric Parameters

Chromaticity Coordinate: $x = 0.3416$ $y = 0.3520$ / $u' = 0.2089$ $v' = 0.4843$ ($duv=1.63e-03$)

CCT= 5139K Prcp WL: $L_d=568.7nm$ Purity=8.1%

Peak WL: $L_p=449nm$ FWHM: $=19.2nm$ Ratio:R=15.5% G=80.0% B=4.5%

Render Index: $R_a = 83.3$ AvgR = 76.6 TM30:Rf=84 Rg=97

EEL: 0.08368 A++ Highest

R1 =82 R2 =87 R3 =91 R4 =84 R5 =83 R6 =83 R7 =87

R8 =69 R9 =10 R10=70 R11=84 R12=64 R13=83 R14=95 R15=77

Photometric & Radiometric Parameters

Flux = 721.10 lm Eff. : 140.56 lm/W Fe = 2.3668 W

Electrical parameters

V = 120.00 V I = 0.04300 A P = 5.130 W PF = 0.9942 F=60.00 Hz

Dongguan New Testing Centre Co., Ltd

3F, No. 1 the 1st North Industry Road, Songshan Lake Science & Technology Park, Dongguan, Guangdong, China