







STREETLIGHT URBAN FDO







	EAN	l x w x h [mm]	W	V _{AC}	Hz	lm	lm/W
URBAN FDO P 40W 722 SYM140	4099854609329	495 x 495 x 970	40	220-240 V	50/60 Hz	4200	105
URBAN FDO P 40W 730 SYM140	4099854609336	495 x 495 x 970	40	220-240 V	50/60 Hz	4800	120
URBAN FDO P 60W 722 SYM140	4099854609343	495 x 495 x 970	60	220-240 V	50/60 Hz	6300	105
URBAN FDO P 60W 730 SYM140	4099854609350	495 x 495 x 970	60	220-240 V	50/60 Hz	7200	120

	EAN	K	IP	IK		R _a	° (°C)	PF	
URBAN FDO P 40W 722 SYM140	4099854609329	2200	66	08	SYM140°	> 70	-20...45	> 0.9	10.8 kg
URBAN FDO P 40W 730 SYM140	4099854609336	3000	66	08	SYM140°	> 70	-20...45	> 0.9	10.8 kg
URBAN FDO P 60W 722 SYM140	4099854609343	2200	66	08	SYM140°	> 70	-20...45	> 0.9	10.8 kg
URBAN FDO P 60W 730 SYM140	4099854609350	3000	66	08	SYM140°	> 70	-20...45	> 0.9	10.8 kg


STREETLIGHT URBAN FDO



STREETLIGHT URBAN FDO




9





URBAN FDO P SET GLASS FROSTED

EAN 4099854618666



	Inrush Current [A]	Th50 [μs]	B10	B16	B25	B32	C10	C16	C25	C32
URBAN FDO P 40W 722 SYM140	18.7	830	4	7	12	15	8	12	20	25
URBAN FDO P 40W 730 SYM140										
URBAN FDO P 60W 722 SYM140	45.9	128	14	22	35	45	22	36	57	73
URBAN FDO P 60W 730 SYM140										



Points de collecte sur www.quefairedemesdechets.fr



LEDVANCE SASU
CQM, 5 rue d'Altorf
67120 Molsheim France
www.ledvance.com

© LEDVANCE Ltd, Sterling House,
810 Mandarin Court, Warrington,
Cheshire, WA1 1GG, United Kingdom

C10449057
G11258131
17.10.25