

CERTIFICATE

No. U6 097386 0741 Rev. 00

Holder of Certificate: **LEDVANCE GmbH**

Parkring 1-5
85748 Garching
GERMANY

Certification Mark:



Product: **Recessed luminaires
(LED Downlight)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142250315301

Date, 2025-08-26

(Michael Xu)



CERTIFICATE

No. U6 097386 0741 Rev. 00

Model(s):

DL CMFT HE D100 P 12W ML 830 OP WT;
DL CMFT HE D100 P 12W ML 840 OP WT;
DL CMFT HE D150 P 15W ML 830 OP WT;
DL CMFT HE D150 P 15W ML 840 OP WT;
DL CMFT HE D200 P 25W ML 830 OP WT;
DL CMFT HE D200 P 25W ML 840 OP WT;
DL CMFT HE D250 P 36W ML 830 OP WT;
DL CMFT HE D250 P 36W ML 840 OP WT;
DL CMFT HE DA D100 P 12W 830 OP WT;
DL CMFT HE DA D100 P 12W 840 OP WT;
DL CMFT HE DA D150 P 15W 830 OP WT;
DL CMFT HE DA D150 P 15W 840 OP WT;
DL CMFT HE DA D200 P 25W 830 OP WT;
DL CMFT HE DA D200 P 25W 840 OP WT;
DL CMFT HE DA D250 P 36W 830 OP WT;
DL CMFT HE DA D250 P 36W 840 OP WT;
DL CMFT HE D100 P 12W ML 830 U19 WT;
DL CMFT HE D100 P 12W ML 840 U19 WT;
DL CMFT HE D150 P 15W ML 830 U19 WT;
DL CMFT HE D150 P 15W ML 840 U19 WT;
DL CMFT HE D200 P 25W ML 830 U19 WT;
DL CMFT HE D200 P 25W ML 840 U19 WT;
DL CMFT HE D250 P 36W ML 830 U19 WT;
DL CMFT HE D250 P 36W ML 840 U19 WT;
DL CMFT HE DA D100 P 12W 830 U19 WT;
DL CMFT HE DA D100 P 12W 840 U19 WT;
DL CMFT HE DA D150 P 15W 830 U19 WT;
DL CMFT HE DA D150 P 15W 840 U19 WT;
DL CMFT HE DA D200 P 25W 830 U19 WT;
DL CMFT HE DA D200 P 25W 840 U19 WT;
DL CMFT HE DA D250 P 36W 830 U19 WT;
DL CMFT HE DA D250 P 36W 840 U19 WT

CERTIFICATE

No. U6 097386 0741 Rev. 00

Brand Name: LEDVANCE



Parameters:

Rated Voltage: 220-240VAC

Rated Frequency: 50/60Hz

Rated Power: See below table for details

Protection Class: II

Degree of Protection: IP20 (for inside ceiling parts);

IP44 (for below ceiling parts)

Blue Light Risk Group: RG1

ta: -20...+40°C

**Tested
according to:**

EN IEC 60598-2-2:2024

EN IEC 60598-1:2021/A11:2022

**Production
Facility(ies):**

088622

CERTIFICATE

No. U6 097386 0741 Rev. 00

Model No.	Rated Power (W)
DL CMFT HE D100 P 12W ML 830 OP WT	7/10/12
DL CMFT HE D100 P 12W ML 840 OP WT	
DL CMFT HE D150 P 15W ML 830 OP WT	10/12/15
DL CMFT HE D150 P 15W ML 840 OP WT	
DL CMFT HE D200 P 25W ML 830 OP WT	15/20/25
DL CMFT HE D200 P 25W ML 840 OP WT	
DL CMFT HE D250 P 36W ML 830 OP WT	25/30/36
DL CMFT HE D250 P 36W ML 840 OP WT	
DL CMFT HE DA D100 P 12W 830 OP WT	7/10/12
DL CMFT HE DA D100 P 12W 840 OP WT	
DL CMFT HE DA D150 P 15W 830 OP WT	10/12/15
DL CMFT HE DA D150 P 15W 840 OP WT	
DL CMFT HE DA D200 P 25W 830 OP WT	15/20/25
DL CMFT HE DA D200 P 25W 840 OP WT	
DL CMFT HE DA D250 P 36W 830 OP WT	25/30/36
DL CMFT HE DA D250 P 36W 840 OP WT	
DL CMFT HE D100 P 12W ML 830 U19 WT	7/10/12
DL CMFT HE D100 P 12W ML 840 U19 WT	
DL CMFT HE D150 P 15W ML 830 U19 WT	10/12/15
DL CMFT HE D150 P 15W ML 840 U19 WT	
DL CMFT HE D200 P 25W ML 830 U19 WT	15/20/25
DL CMFT HE D200 P 25W ML 840 U19 WT	
DL CMFT HE D250 P 36W ML 830 U19 WT	25/30/36
DL CMFT HE D250 P 36W ML 840 U19 WT	
DL CMFT HE DA D100 P 12W 830 U19 WT	7/10/12
DL CMFT HE DA D100 P 12W 840 U19 WT	
DL CMFT HE DA D150 P 15W 830 U19 WT	10/12/15
DL CMFT HE DA D150 P 15W 840 U19 WT	
DL CMFT HE DA D200 P 25W 830 U19 WT	15/20/25
DL CMFT HE DA D200 P 25W 840 U19 WT	
DL CMFT HE DA D250 P 36W 830 U19 WT	25/30/36
DL CMFT HE DA D250 P 36W 840 U19 WT	