



ENVIRONMENTAL PRODUCT DECLARATION

Independent verification of the declaration and data in compliance with ISO 14025

LEDVANCE DAMP PROOF GEN 3 SENSOR

Reference product:

DP SN 1500 P 36W ML 840 VW IP66



Registration number	LEDV-00091-V01.01-EN	Drafting rules	PEP-PCR-ED4-EN-2021 09 06
Verifier accreditation number	VH08	Supplemented by	PSR-0014-ED2.0-EN-2023 07 13
Date of issue	07-2026	Validity period	5 years
EPD prepared by	LEDVANCE GmbH	Information and reference documents:	www.pep-ecopassport.org
Independent verification of the declaration and data in compliance with ISO 14025: 2006			
Internal		External	X
The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain)			
PEP are compliant with XP C08-100-1:2016 or EN 50693:2019			
The elements of the present PEP may not be compared with elements from any other program.			
Document in compliance with ISO 14025: 2006 « Environmental labels and declarations. Type III environmental declarations»			

1. General information

1.1 Company information

Further technical information can be obtained by contacting:

- LEDVANCE GmbH, Parkring 1-5, 85748 Garching, Germany
- or on the website www.ledvance.com
- or by E-Mail LCA@ledvance.com.

1.2 Reference product information

The name of the product under study is DP SN 1500 P 36W ML 840 VW IP66. The assessed product range covers DAMP PROOF from the DAMP PROOF GEN 3 SENSOR product family. Key technical characteristics include IK10 impact resistance, IP66 ingress protection, high luminous efficacy of up to 185 lm/W, and a service lifetime of up to 120,000 hours. The product range offers high versatility through Multi Lumen (ML) functionality, allowing users to select different power and lumen output levels according to project requirements. The key product information is summarized in the table below.

Table 1: Key technological data

Information	
Type of luminaire	DAMP PROOF GEN 3 SENSOR
Short Text Product	DP SN 1500 P 36W ML 840 VW IP66
Operating mode	Integrated LED driver
Lamp type	Integrated LED not exchangeable
Colour temperature [K]	4000
Nominal wattage [W]	36
Luminous flux [lm]	6,400
Luminous efficacy [lm/W]	178 lm/W / 177 lm/W / 180 lm/W
Colour rendering index Ra	> 80
Protection class IK	IK10
Type of protection	IP66
Nominal voltage [V]	220...240 V
Nominal lifetime (L70/B50) [h]	120,000
Length [mm]	1,500
Width [mm]	68
Height / Diameter [mm]	82
Type of Sensor	Brightness & Motion
Area of Application	Indoor applications, Industry (manufacturing plants)

Based on the assigned lifetime according to EN 15193-1:2017 for indoor applications and EN 13201-5:2016 for outdoor applications:

Table 2: Calculated operation lifetime in years per type of building

Type of building	Annual operating hours by default [h]	Operational lifetime [years]
Indoor applications, Industry (manufacturing plants)	4,000	30.0

Following the requirements of the PSR, the operational lifetime of the luminaire of study is 30 years.

1.3 Overview

The general information used for the EPD are listed below:

Table 3: Basic EPD information

Information	
Functional unit	Provide lighting that delivers an outgoing artificial luminous flux of 1,000 lumens during a reference lifetime of 35,000 hours
Reference flow / declared unit*	0.0456 product(s)
Life cycle stages covered (according to EN15804+A2)	Cradle-to-grave and Module D
Product category according to PSR	Luminaires
Product family name (if family EPD)	DAMP PROOF GEN 3 SENSOR

* The reference flow is calculated as:

$$\frac{1,000 \text{ lm}}{\text{Outgoing Luminous Flux of the Analyzed Product (lm)}} \times \frac{35,000 \text{ h}}{\text{Declared Product Lifetime of the Analyzed Product (h)}}$$

Consequently, the reference flow of the following product corresponds to:

$$\frac{1,000}{6,400} \times \frac{35,000}{120,000} = 0.0456$$

1.4 Homogeneous environmental family

The range of variations for the products in the same family are the following:

Table 4: Range of variation for homogeneous environmental family

Criteria	Unit	Value for the reference product	Minimum value in product range	Maximum value in product range
Electrical Power	W	36	26	61
Useful output flux	lm	6,400	4,450	11,000
Weight (Product)	kg	1.794	1.513	1.796
Length	mm	1,500	1,200	1,500

The present PEP declaration is valid for all the products in the described homogenous environmental family. The spreadsheet provided in paragraph 5 Extrapolation of this document shall be used by the PEP user to extrapolate the impact of the other products from the DAMP PROOF GEN 3 SENSOR Family, based on the technical parameters of the considered product, as requested by the PSR.

2 Constituent materials

2.1 Overview

Table 5: Product composition

Information	Weight [kg]	Share [%]
Total weight	2.233	100
Product	1.794	80.4
Packaging	0.438	19.6

2.2 Product

Table 6: Material composition - product

Information	Weight [kg]	Sum of weight [kg]	Share [%]
TOTAL		1.794	100
Metals		0.538	30.0
- Galvanised Steel	0.428		23.8
- Stainless Steel	0.111		6.2
Plastics		0.943	52.6
- PC	0.873		48.6
- Silicone Rubber	0.044		2.4
- PP	0.026		1.5
- PA6	< 0.001		< 0.1
Others		0.313	17.4
- Electronics	0.259		14.4
- Internal & External Wires	0.054		3.0

2.3 Packaging

Table 7: Material composition - packaging

Information	Weight [kg]	Share [%]
TOTAL	0.438	100
Paper/cardboard	0.438	100

Secondary packaging with cardboard is used for shipping. Packaging of raw materials and components is considered as an average quantity of 5 % in mass of the luminaire according to /PSR-0014-ED2.0-EN-2023 07 13/. This additional packaging is not considered in Table 7 as it is an additional assumption.

3 Information on life cycle stages



3.1 Manufacturing

The manufacturer sources all parts from international suppliers. Within the manufacturing site in China, the product is assembled using energy and auxiliaries, if needed. Afterwards the product is packed in packaging materials and distributed to the client. Energy model used in manufacturing is CN: Electricity grid mix, 2021 based on Sphera's Managed LCA Content.



3.2 Distribution

The main market for the product is Europe. For this reason, an Intercontinental transport following PEP-PCR-ed4-EN-2021 09 06 is considered in the model:

- Ship: 19,000 km
- Truck: 1,000 km

The background assumptions for the transportation are listed below.

Table 8: Background information distribution

Information	Unit	Truck	Ship
Fuel type	-	Diesel	Heavy fuel oil
Fuel consumption	l/(kg*km)	2.80E-03	2.30E-04
Total distance	km	1,000	19,000
Capacity utilisation (including empty runs)	%	85	48
Bulk density of transported products	kg/m3	n.a.	n.a.
Volume capacity utilisation factor	-	n.a.	n.a.



3.3 Installation

No energy or material input is required. During installation, the product is unpacked. The packaging materials is treated by applying default values following PSR-0014-ED2.0-EN-2023 07 13.

Table 9: End of life data for packaging in Europe

Treatment scenario	Metal	Paper & Cardboard	Wood	Plastics
Incineration without energy recovery	0 %	0 %	0 %	0 %
Incineration with energy recovery	2 %	9 %	31 %	37 %
Landfill	21 %	9 %	38 %	23 %
Recycling rate	77 %	82 %	31 %	41 %



3.4 Use stage

The product has no direct emissions (B1) and is designed so that no maintenance is required (B2) or parts need to be replaced (B4). Furthermore, no standard repairs (B3) or refurbishments (B5) are foreseen. The use of the product does consume electricity (B6), but no water (B7).

The main market for the product is Europe. Therefore, Energy model used is RER: Electricity grid mix, 2021 based on Sphera's Managed LCA Content. In addition, the reference product contains a component associated with light management function, a motion and light sensor. Therefore, the total energy consumption in B6 is calculated with an energy saving coefficient of 0.55 according to /PSR-0014-ED2.0-EN-2023 07 13/.



3.5 End of life

The product falls under the Waste from Electrical and Electronic Equipment (WEEE) directive 2012/19/EU and its main market is Europe. Therefore, European statistics on the treatment of lighting equipment as subcategory of WEEE from 2018 has been used. No primary energy model is used in End-of-Life Stage. The EoL scenario displays a European average and is the following:

- Incineration without energy recovery: 6.5 %
- Incineration with energy recovery: 7.6 %
- Landfilling: 6.5 %
- Recycling: 79.4 %



3.6 Benefits and loads beyond the system boundaries stage

The incineration with energy recovery and recycling of the product (incl. packaging) generates environmental benefits by avoiding the production of primary materials or energy. The amount and type of material flows used for the calculation of benefits are listed in Table 10.

Table 10: Material flows for Benefits and loads beyond the system boundaries

Information	Unit	Value
Total weight going into re-use	kg/functional unit	0
Total weight going into recycling	kg/functional unit	0.081
- Share of metals	%	24.0
- Share of plastics	%	42.0
- Share of others	%	34.1
Total weight going into incineration with energy recovery	kg/functional unit	0.008
- Share of paper	%	22.4
- Share of others	%	77.6

4 Environmental impacts

4.1 Introduction

The following table summarizes the key information for the calculation of the environmental impacts:

Table 11: Basic information LCA model

Information	Value
Used LCA software	Sphera Solutions, Inc.©, LCA for experts 10
Used LCI database	Sphera Professional 2025.1 + Electronics Extension 2025.1
PCR version	PEP-PCR-ED4-EN-2021 09 06
PSR version	PEP-PSR-0014-ED2.0-EN-2023 07 13
Functional unit	Provide lighting that delivers an outgoing artificial luminous flux of 1,000 lumens during a reference lifetime of 35,000 hours

4.2 Results per functional unit

The following results of the environmental declaration have been developed by considering an outgoing artificial luminous flux of 1,000 lumens over a reference lifetime of 35,000 hours. The results refer to the core environmental impact indicators and indicators describing resource use, waste categories, and output flows according to EN 15804:2012+A2:2019.

Table 12: Results for core environmental impact indicators per functional unit

	Total (excl. D)	Raw materials & parts		Manufac- turing	Distribu- tion	Install- ation	Use	End of life			Benefits and loads beyond the system boundaries
		A1	A2	A3	A4	A5	B6	C2	C3	C4	D
GWP - total [kg CO ₂ eq.]	3.56E+01	8.27E-01	6.36E-03	-1.35E-03	2.81E-02	1.61E-02	3.47E+01	5.99E-03	9.92E-02	3.94E-03	-1.21E-01
GWP - fossil [kg CO ₂ eq.]	3.52E+01	8.28E-01	6.34E-03	2.50E-02	2.80E-02	9.84E-03	3.42E+01	5.97E-03	9.92E-02	3.93E-03	-1.45E-01
GWP - biogenic [kg CO ₂ eq.]	3.28E-01	-3.11E-03	-4.08E-05	-2.65E-02	-2.71E-05	6.23E-03	3.52E-01	-3.85E-05	2.23E-05	-3.87E-08	2.45E-02
GWP - luluc [kg CO ₂ eq.]	1.15E-01	1.61E-03	6.62E-05	1.59E-04	7.82E-05	3.57E-05	1.13E-01	6.23E-05	8.73E-06	1.21E-06	-2.83E-04
ODP [kg CFC-11 eq.]	7.89E-10	9.22E-12	1.07E-15	8.55E-14	3.20E-15	2.61E-14	7.79E-10	1.00E-15	6.64E-14	2.03E-15	-1.97E-12
AP [Mole of H ⁺ eq.]	7.95E-02	3.97E-03	1.16E-05	7.64E-05	4.62E-04	2.59E-05	7.49E-02	1.09E-05	2.67E-05	3.55E-06	-1.47E-03
EP - freshwater [kg P eq.]	7.94E-05	5.57E-06	1.73E-08	3.85E-07	2.56E-08	2.22E-07	7.31E-05	1.63E-08	1.36E-08	8.74E-10	-4.22E-07
EP - marine [kg N eq.]	1.88E-02	5.90E-04	4.91E-06	3.48E-05	1.66E-04	1.38E-05	1.80E-02	4.62E-06	8.11E-06	1.52E-06	-1.30E-04
EP - terrestrial [Mole of N eq.]	2.10E-01	6.31E-03	5.24E-05	3.23E-04	1.82E-03	1.17E-04	2.01E-01	4.93E-05	1.24E-04	1.78E-05	-1.39E-03
POCP [kg NMVOC eq.]	4.70E-02	1.84E-03	1.04E-05	6.94E-05	4.56E-04	2.13E-05	4.46E-02	9.78E-06	2.15E-05	3.98E-06	-4.00E-04
ADPE [kg Sb eq.]	8.41E-05	7.70E-05	4.28E-10	9.98E-09	1.02E-09	6.81E-09	7.11E-06	4.03E-10	5.78E-10	2.26E-11	-3.51E-05
ADPF [MJ]	7.11E+02	1.19E+01	8.24E-02	3.07E-01	3.38E-01	1.33E-01	6.98E+02	7.76E-02	9.95E-02	4.67E-03	-2.01E+00
WDP [m ³ world equiv.]	8.77E+00	1.69E-01	2.94E-05	1.16E-02	7.28E-05	1.33E-03	8.57E+00	2.77E-05	1.10E-02	8.53E-04	-3.41E-02

Table 13: Results for indicators describing resource use, waste categories, and output flows per functional unit

Indicator	Acronym [Unit]	Value
Renewable primary energy (without raw material)	PERE [MJ]	4.80E+02
Renewable primary energy (raw material)	PERM [MJ]	3.59E-01
Total use of renewable primary energy	PERT [MJ]	4.80E+02
Non-renewable primary energy (without raw material)	PENRE [MJ]	7.08E+02
Non-renewable primary energy (raw material)	PENRM [MJ]	1.25E+00
Total use of non-renewable primary energy	PENRT [MJ]	7.09E+02
Use of secondary materials	SM [kg]	3.30E-02
Use of renewable secondary fuels	RSF [MJ]	0.00E+00
Use of non-renewable secondary fuels	NRSF [MJ]	0.00E+00
Net use of fresh water	FW [m3]	8.73E+00
Hazardous waste disposed	HWD [kg]	9.38E-07
Non-hazardous waste disposed	NHWD [kg]	5.91E-01
Radioactive waste disposed	RWD [kg]	1.10E-01
Components for reuse	CRU [kg]	0.00E+00
Materials for recycling	MFR [kg]	4.19E-02
Materials for energy recovery	MER [kg]	4.37E-02
Exported electricity	EEE [MJ]	1.66E-01
Exported thermal energy	EET [MJ]	3.74E-01
Biogenic carbon content of the product	Biog. C in product [kg]	0.00E+00
Biogenic carbon content of the associated packaging	Biog. C in packaging [kg]	8.58E-03

4.3 Results per unit of product

The following results of the environmental declaration have been developed by considering the entire life cycle of one product with the technical properties described in paragraph 1.

Table 14: Results core environmental impact indicators per unit of product

	Total (excl. D)	Raw materials & parts		Manufac- turing	Distribu- tion	Install- ation	Use	End of life			Benefits and loads beyond the system boundaries
		A1	A2	A3	A4	A5	B6	C2	C3	C4	D
GWP - total [kg CO2 eq.]	7.82E+02	1.81E+01	1.40E-01	-2.95E-02	6.16E-01	3.53E-01	7.61E+02	1.31E-01	2.18E+00	8.64E-02	-2.65E+00
GWP - fossil [kg CO2 eq.]	7.72E+02	1.82E+01	1.39E-01	5.48E-01	6.15E-01	2.16E-01	7.50E+02	1.31E-01	2.18E+00	8.63E-02	-3.19E+00
GWP - biogenic [kg CO2 eq.]	7.20E+00	-6.82E-02	-8.96E-04	-5.81E-01	-5.94E-04	1.37E-01	7.71E+00	-8.44E-04	4.90E-04	-8.50E-07	5.38E-01
GWP - luluc [kg CO2 eq.]	2.52E+00	3.53E-02	1.45E-03	3.48E-03	1.72E-03	7.83E-04	2.48E+00	1.37E-03	1.92E-04	2.66E-05	-6.21E-03
ODP [kg CFC-11 eq.]	1.73E-08	2.02E-10	2.34E-14	1.88E-12	7.02E-14	5.72E-13	1.71E-08	2.20E-14	1.46E-12	4.46E-14	-4.33E-11
AP [Mole of H+ eq.]	1.74E+00	8.72E-02	2.54E-04	1.68E-03	1.01E-02	5.67E-04	1.64E+00	2.39E-04	5.86E-04	7.80E-05	-3.22E-02
EP - freshwater [kg P eq.]	1.74E-03	1.22E-04	3.80E-07	8.46E-06	5.61E-07	4.86E-06	1.60E-03	3.58E-07	2.98E-07	1.92E-08	-9.26E-06
EP - marine [kg N eq.]	4.12E-01	1.30E-02	1.08E-04	7.63E-04	3.64E-03	3.03E-04	3.94E-01	1.01E-04	1.78E-04	3.33E-05	-2.85E-03
EP - terrestrial [Mole of N eq.]	4.61E+00	1.39E-01	1.15E-03	7.09E-03	3.98E-02	2.56E-03	4.42E+00	1.08E-03	2.73E-03	3.91E-04	-3.04E-02
POCP [kg NMVOC eq.]	1.03E+00	4.03E-02	2.28E-04	1.52E-03	1.00E-02	4.68E-04	9.78E-01	2.15E-04	4.72E-04	8.73E-05	-8.79E-03
ADPE [kg Sb eq.]	1.85E-03	1.69E-03	9.38E-09	2.19E-07	2.23E-08	1.49E-07	1.56E-04	8.83E-09	1.27E-08	4.96E-10	-7.70E-04
ADPF [MJ]	1.56E+04	2.61E+02	1.81E+00	6.74E+00	7.41E+00	2.92E+00	1.53E+04	1.70E+00	2.18E+00	1.02E-01	-4.41E+01
WDP [m³ world equiv.]	1.92E+02	3.72E+00	6.45E-04	2.54E-01	1.60E-03	2.91E-02	1.88E+02	6.07E-04	2.41E-01	1.87E-02	-7.48E-01

Table 15: Results indicators describing resource use, waste categories, and output flows per unit of product

Indicator	Acronym [Unit]	Value
Renewable primary energy (without raw material)	PERE [MJ]	1.05E+04
Renewable primary energy (raw material)	PERM [MJ]	7.89E+00
Total use of renewable primary energy	PERT [MJ]	1.05E+04
Non-renewable primary energy (without raw material)	PENRE [MJ]	1.55E+04
Non-renewable primary energy (raw material)	PENRM [MJ]	2.75E+01
Total use of non-renewable primary energy	PENRT [MJ]	1.56E+04
Use of secondary materials	SM [kg]	7.25E-01
Use of renewable secondary fuels	RSF [MJ]	0.00E+00
Use of non-renewable secondary fuels	NRSF [MJ]	0.00E+00
Net use of fresh water	FW [m3]	1.92E+02
Hazardous waste disposed	HWD [kg]	2.06E-05
Non-hazardous waste disposed	NHWD [kg]	1.30E+01
Radioactive waste disposed	RWD [kg]	2.42E+00
Components for reuse	CRU [kg]	0.00E+00
Materials for recycling	MFR [kg]	9.20E-01
Materials for energy recovery	MER [kg]	9.60E-01
Exported electricity	EEE [MJ]	3.65E+00
Exported thermal energy	EET [MJ]	8.21E+00
Biogenic carbon content of the product	Biog. C in product [kg]	0.00E+00
Biogenic carbon content of the associated packaging	Biog. C in packaging [kg]	1.88E-01

5 Extrapolation

5.1 Extrapolation rules

Extrapolations rules have been calculated following PCR-ed4-EN-2021 09 14 and PSR-0014-ed2.0- EN-2023 07 18. The defined rules shall be applied using the Extrapolation rules file provided in the following tables.

Table 16: Extrapolation parameters for reference product

Parameter	Value for reference product (DP SN 1500 P 36W ML 840 VW IP66)
Lighting output [lm]	6,400
Weight of light source [kg]	0.064
Weight of luminaire structure [kg]	1.551
Weight of control gear [kg]	0.141
Weight of light management system [kg]	0.039
Weight of packaging [kg]	0.438
Power [W]	36
Length [mm]	1,500
Height [mm]	82
Width [mm] / Diameter [mm]	68

The extrapolation coefficients calculation at the functional unit level shall be taken into account with the following formula:

$$\text{Extrapolation coefficient at the product level} \times \frac{\text{Lighting output of reference product (lm)}}{\text{Lighting output of concerned product (lm)}}$$

5.2 Extrapolation coefficients

The reported extrapolation coefficients are intended at product level (declared unit) and not at functional unit.

- Products in this product family, including the reference product, are equipped with motion and light sensors and hence are assigned with an energy-saving coefficient of 0.55.

Table 17: Calculated Extrapolation coefficients per product

Product Name	Useful out-put flux [lm]	Manufac-turing	Distribu-tion	Installa-tion	Use	EoL
DP SN 1500 P 36W ML 840 VW IP66	6,400	1.00	1.00	1.00	1.00	1.00
DP SN 1200 P 26W ML 830 VW IP66	4,450	0.88	0.85	0.86	0.72	0.84
DP SN 1200 P 26W ML 840 VW IP66	4,600	0.88	0.85	0.86	0.72	0.84
DP SN 1200 P 26W ML 865 VW IP66	4,600	0.88	0.85	0.86	0.72	0.84
DP SN 1500 P 36W ML 830 VW IP66	6,150	1.02	1.00	1.00	1.00	1.00
DP SN 1500 P 36W ML 865 VW IP66	6,400	1.02	1.00	1.00	1.00	1.00
DP SN 1500 P 61W ML 830 VW IP66	10,400	1.02	1.00	1.00	1.69	1.00
DP SN 1500 P 61W ML 840 VW IP66	11,000	1.02	1.00	1.00	1.69	1.00
DP SN 1500 P 61W ML 865 VW IP66	11,000	1.02	1.00	1.00	1.69	1.00