



LEDVANCE Pty Ltd
Unit 3, 83 Derby St
Silverwater NSW 2128
Customer Service
Phone: 1300 467 726
E-mail: sales.au@ledvance.com

ARCHIGLOW DOWNLIGHT



ARCHIGLOW DOWNLIGHT

Introducing the ArchiGlow Downlight – the perfect blend of performance and aesthetics. Featuring tri-colour selection (3000K/3500K/4000K), it offers flexibility for any space. Choose between fixed or gimbal designs to suit your installation needs. With flicker-free operation, high colour rendering (CRI >90), and low glare (UGR <19), it ensures superior visual comfort. Consistent colour accuracy is guaranteed with SDCM <3 at 3000K and 4000K. Ideal for modern interiors, the ArchiGlow delivers professional lighting with architectural appeal.



FEATURES AND BENEFITS

- Tri colour selectable: 3000/3500/4000K
- Available in both fixed and gimbal designs to suit general lighting or directional accent applications
- Flicker-free light for better visual comfort and eye protection
- CRI >90 for accurate and vibrant colour rendering
- UGR <19 to reduce glare in work or study areas
- SDCM <3 at 3000K and 4000K for consistent colour output
- DALI 2.0 optional for advanced dimming and control integration

AREAS OF APPLICATION

- Premium residential estates
- Hospitality venues
- Architectural lighting
- High-end commercial spaces
- Retail stores



AVAILABLE DESIGN

FIX



LDLA10WFWH
Cut-out Ø90mm
Diameter Ø105mm x H 84mm



LDLA10WFBK
Cut-out Ø90mm
Diameter Ø105mm x H 84mm

GIMBAL



LDLA10WGWH
Cut-out Ø90mm
Diameter Ø104mm x H 91mm



LDLA10WGBK
Cut-out Ø90mm
Diameter Ø104mm x H 91mm

SPECIFICATIONS



lm/W	92 lm/W
CCT	3000/3500/4000K
IC Rating	IC-4
IP Rating	IP54
Dimmable	Phase-cut dim, DALI2.0 (Optional)
Double Insulated	Yes
Housing Material	Die-cast Aluminium
Beam Angle	60°
Tilt Angle	0-20° (Gimbal version only)
CRI	>90
UGR	<19
SDCM	<3 @ 3000K & 4000K

Electrical Classification	Class II
Connection Type	1m Flex & Plug (Inclusive of fast connector)
Voltage	220-240V
Input Current	48.3 mA
PF	≥0.9
Frequency	50/60Hz
Flicker Rate	Flicker Free
Installation Type	Recessed
Operating Temperature	-20°C to 45°C
Lifetime	50,000 hours
Warranty	5 years

PHOTOMETRICS

(Example of)

DIMENSIONS



Model	Cut-out (mm)	Diameter (mm)	H (mm)
LDLA10WFWH	Ø90	Ø105	84
LDLA10WFBK	Ø90	Ø105	84

Model	Cut-out (mm)	Diameter (mm)	H (mm)
LDLA10WGWH	Ø90	Ø104	91
LDLA10WGBK	Ø90	Ø104	91

ORDERING CODES - ARCHIGLOW DOWNLIGHT

Model number* (Order Code)	EAN10	Description	W	lm ¹	K		lm/W	CUT OUT (mm)	Ø (mm)	h (mm)
-------------------------------	-------	-------------	---	-----------------	---	---	------	-----------------	-----------	-----------

ARCHIGLOW FIX DOWNLIGHT

LDLA10WFWH	4099854607929	ARCHIGLOW FIX DOWNLIGHT TC 10W UPTO 920LM C090MM CRI90 IC-4 DIM COB UGR19 3K/3.5K/4K BEAM60D REMOTE FLICKERFREE DRIVER IP54 SDCM3 WHITE	10	920	3000/ 3500/ 4000	60	92	90	105	84
LDLA10WFBK	4099854607943	ARCHIGLOW FIX DOWNLIGHT TC 10W UPTO 920LM C090MM CRI90 IC-4 DIM COB UGR19 3K/3.5K/4K BEAM60D REMOTE FLICKERFREE DRIVER IP54 SDCM3 BLACK	10	920	3000/ 3500/ 4000	60	92	90	105	84

ARCHIGLOW GIMBAL DOWNLIGHT

LDLA10WGWH	4099854607967	ARCHIGLOW GIMBAL DOWNLIGHT TC 10W UPTO 920LM C090MM CRI90 IC-4 DIM COB UGR19 3K/3.5K/4K BEAM60D REMOTE FLICKERFREE DRIVER IP54 SDCM3 WHITE	10	920	3000/ 3500/ 4000	60	92	90	104	91
LDLA10WGBK	4099854607981	ARCHIGLOW GIMBAL DOWNLIGHT TC 10W UPTO 920LM C090MM CRI90 IC-4 DIM COB UGR19 3K/3.5K/4K BEAM60D REMOTE FLICKERFREE DRIVER IP54 SDCM3 BLACK	10	920	3000/ 3500/ 4000	60	92	90	104	91

*Denotes of Model Number: L-LEDVANCE; DLA-Downlight ArchiGlow; 10W-10Watts; F-Fix Head; G-Gimbal Head; WH-White Finish; BK-Black Finish

1 The Rated Lumen outputs are specified @3500/4000K. Lumen outputs @3000K is 8% less than the above rated lumen outputs respectively.