



LEDVANCE Pty Ltd
Unit 3, 83 Derby St
Silverwater NSW 2128
Customer Service
Phone: 1300 467 726
E-mail: sales.au@ledvance.com

ECO IP65 WIDE BODY BATTEN



ECO IP65 WIDE BODY BATTEN

The ECO IP65 Wide Body Batten delivers flexible performance with selectable wattage (40/35/30/20W) and tri-colour options (3000K/4000K/5700K). Its 115mm wide body is ideal for retrofits, easily covering existing ceiling marks. Featuring a two-piece design with an encapsulated module, it enables quick, hassle-free installation. Flicker-free illumination provides stable and comfortable lighting. The removable 6mm PA16 terminal block ensures simple, secure wiring. With an optional emergency version available, this durable batten is a smart choice for efficient and adaptable lighting solutions.



FEATURES AND BENEFITS

- Multi-watt selectable: 40/35/30/20W
- Tri colour selectable: 3000K/4000K/5700K
- 115mm Wide body fits retrofits perfectly and hides old ceiling marks
- Two-piece construction with encapsulated module for quick and hassle-free installation
- Flicker free for comfortable, stable lighting
- Available with emergency option
- Removable 6mm PA16 terminal block allows fast, easy wiring and secure connections

AREAS OF APPLICATION

- Car parks
- Public areas
- Warehouses
- Railways
- Commercial spaces



AVAILABLE SIZES



4FT
LWPE4F40MW
40/35/30/20W
L 1255mm x W 115mm x H 85mm

SPECIFICATIONS


lm/W	100 lm/W
CCT	3000/4000/5700
IP Rating	IP65
IK Rating	IK08
Housing Material	Polycarbonate Stainless Steel clips and screws
Beam Angle	120°
CRI	>80
SDCM	<6
Electrical Classification	Class I
Connection Type	PA16 Terminal

Voltage	220-240V
Input Current	40W: 193mA
Inrush Current	17.5A@195µs (230V AC)
PF	>0.9
Frequency	50/60Hz
Surge Protection	1KV
Flicker Rate	Flicker Free
Installation Type	Surface
Operating Temperature	-30°C to 50°C
Lifetime	50000 hours
Warranty	4 years

PHOTOMETRICS

(Example of)

DIMENSIONS



4FT
LWPE4F40MW
40/35/30/20W
L 1255mm x W 115mm x H 85mm

ORDERING CODES - ECO IP65 WIDE BODY BATTEN

Model number* (Order Code)	EAN10	Description	W	lm ¹	K	lm/W	$\frac{l}{mm}$	$\frac{w}{mm}$	$\frac{h}{mm}$
-------------------------------	-------	-------------	---	-----------------	---	------	----------------	----------------	----------------

STANDARD

LWPE4F40MW	4099854612077	ECO WEATHERPROOF BATTEN TC 4FT MW 40/35/30/20W UPTO 100LM/W 4000LM IP65 IK08 FLICKERFREE 3K/4K/5.7K L1255XW115XH85MM	40/ 35/ 30/ 20	4000	3000/ 4000/ 5700	100	1255	115	85
------------	---------------	---	-------------------------	------	------------------------	-----	------	-----	----

EMERGENCY



LWPE4F40MWEM	4099854612091	ECO WEATHERPROOF EMG BATTEN TC 4FT MW 40/35/30/20W UPTO 100LM/W 4000LM IP65 IK08 FLICKERFREE 3K/4K/5.7K L1255XW115XH85MM	40/ 35/ 30/ 20	4000	3000/ 4000/ 5700	100	1255	115	85
--------------	---------------	---	-------------------------	------	------------------------	-----	------	-----	----

*Denotes of Model Number: L-LEDVANCE; WP-WeatherProof; E-ECO;4F-4FT;40MW-Multi Watt up to 40W ;EM-Emergency

¹ The Rated Lumen outputs are specified @4000K/5700K. Lumen outputs @3000K is 8% less than the above rated lumen outputs respectively.