

LEDVANCE.COM.AU



LEDVANCE

LEDVANCE Pty Ltd
Unit 3, 83 Derby St
Silverwater NSW 2128
Customer Service
Phone: 1300 467 726
E-mail: sales.au@ledvance.com

LUXEWAY BOLLARD



VERSION 05/08/25

LUXEWAY BOLLARD

Introducing the LuxeWay Bollard – a sleek and modern outdoor lighting solution built for performance and resilience. Available in two height options – 540mm and 996mm – its stylish bollard design features multi-watt selectable (22W/16W/11W) and tri-colour selectable options (3000K/4000K/5000K), delivering an impressive 140 lm/W. Engineered for harsh conditions, it is IP66 and IK10 rated, corrosion resistant, and flicker free. Optional DALI2.0 compatibility and a wide range voltage input ensure flexible control and reliable operation, making it perfect for pathways, parks, and commercial outdoor spaces.



FEATURES AND BENEFITS

- Multi-watt selectable: 22/16/11W
- Tri colour selectable: 3000/4000/5000K
- Stylish bollard design complements modern outdoor spaces
- 140 lm/W efficiency reduces energy use with strong light output
- IP66 and IK10 ratings ensure weather and impact resistance
- Flicker free lighting enhances visual comfort and safety
- Corrosion resistant build suits coastal and outdoor areas
- Wide voltage range (120-277V) supports flexible installation
- DALI2.0 optional for advanced lighting control systems

AREAS OF APPLICATION

- Pathways & Walkway
- Driveways & Parking Lots
- Parks & Gardens
- Commercial Complexes
- Hotel & Resort Entrances



AVAILABLE SIZES



LBL22MW2F
22/16/11W
Diameter Ø160mm x H 540mm



LBL22MW4F
22/16/11W
Diameter Ø160mm x H 996mm


SPECIFICATIONS

lm/W	140lm/W	Driver Technology	Constant Current Isolation Driver
CCT	3000/4000/5000K	Voltage	120-277V
IP Rating	IP65	PF	>0.9
IK Rating	IK10	Frequency	50/60Hz
Dimmable	DALI2.0 (optional)	Surge Protection	L/N: 2KV, L/N-PE: 4KV
Sensor	Optional	Corrosion Resistant	Yes
Housing Material	Aluminium	Flicker Rate	Flicker Free
Beam Angle	360°	Installation Type	Rag-bolt assembly accessory included
CRI	>70	Operating Temperature	-30°C to 50°C
SDCM	<6	Lifetime	50,000h
Electrical Classification	Class I	Warranty	5 years
Connection Type	Terminal Block		

PHOTOMETRICS

(Example of)

DIMENSIONS



Model	Diameter (mm)	H (mm)
LBL22MW2F	Ø160	540
LBL22MW4F	Ø160	996

ORDERING CODES - LUXEWAY BOLLARD

Model number* (Order Code)	EAN10	Description							
-------------------------------	-------	-------------	--	---	---	---	---	---	---

LUXEWAY BOLLARD

LBL22MW2F	4099854526626	LUXEWAY BOLLARD TC MW 22/16/11W	22/	3080/	3000/				
		UPTO 140LM/W 3080LM IP66 IK10 3K/4K/5K	16/	2240/	4000/	360	140	160	540
		H540*D160MM BLACK	11	1540	5000				
LBL22MW4F	4099854526633	LUXEWAY BOLLARD TC MW 22/16/11W	22/	3080/	3000/				
		UPTO 140LM/W 3080LM IP66 IK10 3K/4K/5K	16/	2240/	4000/	360	140	160	996
		H996*D160MM BLACK	11	1540	5000				

*Denotes of Model Number: L-LEDVANCE; BL-Bollard; 22MW-Multi Watt up to 22W; 2F-540mm; 4F-996mm

1 The Rated Lumen outputs are specified @4000K/5000K. Lumen outputs @3000K is 8% less than the above rated lumen outputs respectively.