LEDVANCE.COM.AU



LEDVANCE Pty Ltd Unit 3, 83 Derby St Silverwater NSW 2128 Customer Service Phone: 1300 467 726

E-mail: sales.au@ledvance.com



OVALITE BUNKER

The Ovalite Bunker is a robust 15W oval-shaped fixture delivering 100lm/W efficiency and tri colour selectable output (3000K/4000K/5000K), ideal for versatile lighting applications. Designed for durability, it features an impact-resistant IK10 and weatherproof IP65 rating. Its flexible installation is supported by both side and rear cable entry options, along with a large PA16 terminal block for easy wiring. A flicker-free driver ensures visual comfort, making it a reliable solution for both indoor and outdoor environments.





FEATURES AND BENEFITS

- Tri colour selectable: 3000/4000/5000K
- IK10 impact resistance for high durability
- Allows flexible wiring with both sides and rear cable entry points
- Equipped with a PA16 large terminal block for easy installation
- · Includes a flicker-free driver for enhanced visual comfort
- Rated IP65 for protection against dust and water
- Delivers high efficiency with 100 lm/W

AREAS OF APPLICATION

- Public spaces
- Gardens and pathways
- Sheltered outdoor areas
- Corridors, stairways, and entrance areas













AVAILABLE SIZES



LBU15WTC 15W L 345mm X W 190mm X H 80mm

SPECIFICATIONS


lm/W	100 lm/W				
ССТ	3000/4000/5000K				
IP Rating	IP65				
IK Rating	IK10				
Double Insulated	Yes				
Housing Material	PC				
Beam Angle	110°				
CRI	>80				
SDCM	<5				
Electrical Classification	Class II				

Connection Type	PA16 Terminal Block				
Voltage	220-240V				
PF	>0.9				
Frequency	50/60Hz				
Flicker Rate	Flicker Free				
Installation Type	Surface mount				
Operating Temperature	-30°C to 50°C				
Lifetime	50,000 hours				
Warranty	5 years				

PHOTOMETRICS

(Example of)

DIMENSIONS



LBU15WTC 15W L 345mm X W 190mm X H 80mm

ORDERING CODES - OVALITE BUNKER

Model number* (Order Code)	EAN10	Description	W	lm ¹	K		lm/w	[mm]	w [mm]	h _[mm]
OVALITE BUNKER										
LBU15WTC	4099854616167	OVALITE TC BUNKER 15W 1500LM IK10 FLICKERFREE MULTI-ENTRY IP65 3K/4K/5K BLACK	15	1500	3000/ 4000/ 5000	110	100	50	50	61

^{*}Denotes of Model Number: L-LEDVANCE; BU-Bunker; 15W-15Watts;TC-Tri Colour

¹ The Rated Lumen outputs are specified @4000/5000K. Lumen outputs @3000K is 8% less than the above rated lumen outputs respectively.