



LEDVANCE Pty Ltd  
Unit 3, 83 Derby St  
Silverwater NSW 2128  
Customer Service  
Phone: 1300 467 726  
E-mail: sales.au@ledvance.com

# VALITE CRI90 UGR19 DOWNLIGHT



# VALITE CRI90 UGR19 DOWNLIGHT

The VALITE CRI90 UGR19 Downlight offers premium visual comfort with a deep reflector design and  $UGR < 19$ , ideal for glare-free lighting. It features tri colour selection (3000K/4000K/5700K) for adaptable ambience and a high  $CRI > 90$  for true colour rendering. With a standard 90mm cut-out, it suits most ceiling types and is IC-4 rated for safe insulation contact. Double insulated for added safety, it's available in white or black finishes, making it perfect for residential and commercial settings.



## FEATURES AND BENEFITS

- Tri colour selectable: 3000K/4000K/5700K
- High  $CRI > 90$  delivers excellent colour accuracy and natural-looking light
- Low glare design with  $UGR < 19$  ensures enhanced visual comfort, ideal for offices and living spaces
- Available in stylish white or black finishes to suit various interior designs
- Deep reflector design reduces glare and adds a modern aesthetic
- Equipped with a flicker-free integrated driver for visual comfort

## AREAS OF APPLICATION

- Offices
- Residential spaces
- Hospitality venues
- Commercial spaces



## AVAILABLE DESIGN



White  
LDLV9WWH  
9W  
Cut-out  $\varnothing 90\text{mm}$   
Diameter  $\varnothing 100\text{mm}$  x H 85mm




Black  
LDLV9WBK  
9W  
Cut-out  $\varnothing 90\text{mm}$   
Diameter  $\varnothing 100\text{mm}$  x H 85mm

## SPECIFICATIONS


<b>lm/W</b>	89 lm/W	<b>Electrical Classification</b>	Class II
<b>CCT</b>	3000/4000/5700K	<b>Connection Type</b>	0.6m Flex & Plug
<b>IC Rating</b>	IC-4	<b>Voltage</b>	220-240V
<b>IP Rating</b>	IP54	<b>PF</b>	0.9
<b>Dimmable</b>	Yes	<b>Frequency</b>	50/60Hz
<b>Double Insulated</b>	Yes	<b>Flicker Rate</b>	Flicker Free
<b>Housing Material</b>	Polycarbonate	<b>Installation Type</b>	Recessed
<b>Beam Angle</b>	60°	<b>Operating Temperature</b>	-20°C to 40°C
<b>CRI</b>	>90	<b>Lifetime</b>	35000 hours
<b>SDCM</b>	<4 @3000K & 5700K <5 @4000K	<b>Warranty</b>	5 years
<b>UGR</b>	<19		

## PHOTOMETRICS

(Example of LDLV9WWH)



## DIMENSIONS



9W  
Cut-out  $\varnothing 90\text{mm}$   
Diameter  $\varnothing 100\text{mm}$  x H 85mm

ORDERING CODES - VALITE CRI90 UGR19 DOWNLIGHT

Model number* (Order Code)	EAN10	Description	W	lm <sup>1</sup>	K		lm/W			CUT OUT (mm)		
-------------------------------	-------	-------------	---	-----------------	---	--	------	--	--	-----------------	--	--

WHITE

LDLV9WWH	4099854613081	VALITE DOWNLIGHT TC 9W UPTO 800LM UGR19 CRI90 IC-4 FLICKERFREE DIM IP54 CO90MM 3K/4K/5.7K BEAM60D DEEP REFLECTOR WHITE	9	800	3000/ 4000/ 5700	60	89	✓		90	100	85
----------	---------------	---	---	-----	------------------------	----	----	---	--	----	-----	----

BLACK

LDLV9WBK	4099854613074	VALITE DOWNLIGHT TC 9W UPTO 800LM UGR19 CRI90 IC-4 FLICKERFREE DIM IP54 CO90MM 3K/4K/5.7K BEAM60D DEEP REFLECTOR BLACK	9	800	3000/ 4000/ 5700	60	89	✓		90	100	85
----------	---------------	---	---	-----	------------------------	----	----	---	--	----	-----	----

\*Denotes of Model Number: L-LEDVANCE; DLV-Downlight Valite; 9W-9Watt; WH-White; BK-Black

1 The Rated Lumen outputs are specified @4000K/5700K. Lumen outputs @3000K is 8% less than the above rated lumen outputs respectively.