



LEDVANCE Pty Ltd
Unit 3, 83 Derby St
Silverwater NSW 2128
Customer Service
Phone: 1300 467 726
E-mail: sales.au@ledvance.com

VILLAGLOW DOWNLIGHT



VILLAGLOW DOWNLIGHT

The VillaGlow Downlight combines performance and style with tri-colour (3000K/3500K/4000K) and is available in three cut-out sizes: 70mm (9W), 90mm (12W), and 120mm (20W). Featuring a sleek deep-set design for a modern architectural look, it comes in both white and black finishes. Experience high-quality lighting with CRI>90, low glare (UGR<19), and SDCM<3 for consistent colour. The flicker-free output ensures visual comfort, and its IC-4 rating allows safe insulation contact—making VillaGlow ideal for residential, commercial, and retail applications.



FEATURES AND BENEFITS

- Tri colour selectable: 3000K/3500K/4000K
- Deep-set design reduces glare and adds a modern look
- Available in white and black options, offering finishes to match any décor
- UGR<19 reduces glare, ensuring eye comfort
- CRI>90 provides high colour rendering for vibrant, true-to-life lighting
- SDCM<3 @ 3000K and 4000K ensures consistent colour quality with minimal variation
- Flicker-free design provides stable, comfortable lighting
- DALI 2.0 optional for advanced dimming and control integration

AREAS OF APPLICATION

- Premium residential estates
- Hospitality venues
- Architectural lighting
- High-end commercial spaces
- Retail stores



AVAILABLE SIZES



LDLP9W
9W
Cut-out Ø72mm
Diameter Ø81mm x H 97mm



LDLP12W
12W
Cut-out Ø90mm
Diameter Ø98mm x H 92mm



LDLP20W
20W
Cut-out Ø120mm
Diameter Ø130mm x H 98mm

AVAILABLE COLOUR



White




Black

SPECIFICATIONS



lm/W	80-100 lm/W	Electrical Classification	Class I
CCT	3000/3500/4000K	Connection Type	1m Flex & Plug (In-line with fast connector)
IC Rating	IC-4	Voltage	220-240V
IP Rating	IP54(Front)	PF	≥0.9
Dimmable	Phase dimming, DALI2.0 (optional)	Frequency	50/60Hz
Double Insulated	Yes	Flicker Rate	Flicker Free
Housing Material	Die-cast Aluminium	Installation Type	Recessed
Beam Angle	60°	Operating Temperature	-20°C to 40°C
CRI	>90	Lifetime	50,000 hours
SDCM	<3 @3000K & 4000K <5 @3500K	Warranty	5 years
UGR	<19		

PHOTOMETRICS

(Example of LDLP9WWH @9W)



DIMENSIONS



Model	Cut-out (mm)	Diameter (mm)	H (mm)
LDLP9W	Ø72	Ø81	97
LDLP12W	Ø90	Ø98	92
LDLP20W	Ø120	Ø130	98

ORDERING CODES - VILLAGLOW DOWNLIGHT

Model number* (Order Code)	EAN10	Description	W	lm	K		lm/W	CUT OUT (mm)		
WHITE										
LDLP9WWH	4099854514210	VILLAGLOW DOWNLIGHT TC 9W UPTO 720LM C072MM UGR19 CRI90 SDCM3 IC-4 FLICKERFREE DIM IP54 3K/3.5K/4K BEAM60D DEESET WHITE	9	720	3000/ 3500/ 4000	60	80	72	81	97
LDLP12WWH	4099854514258	VILLAGLOW DOWNLIGHT TC 12W UPTO 1020LM CRI90 C090MM UGR19 SDCM3 IC-4 FLICKERFREE DIM IP54 3K/3.5K/4K BEAM60D DEESET WHITE	12	1020	3000/ 3500/ 4000	60	85	90	96	92
LDLP20WWH	4099854514296	VILLAGLOW DOWNLIGHT TC 20W 2000LM CRI90 C0120MM UGR19 SDCM3 IC-4 FLICKERFREE DIM IP54 3K/3.5K/4K BEAM60D DEESET WHITE	20	2000	3000/ 3500/ 4000	60	100	120	130	98
BLACK										
LDLP9WBK	4099854514234	VILLAGLOW DOWNLIGHT TC 9W UPTO 720LM C072MM UGR19 CRI90 SDCM3 IC-4 FLICKERFREE DIM IP54 3K/3.5K/4K BEAM60D DEESET BLACK	9	720	3000/ 3500/ 4000	60	80	72	81	97
LDLP12WBK	4099854514272	VILLAGLOW DOWNLIGHT TC 12W UPTO 1020LM CRI90 C090MM UGR19 SDCM3 IC-4 FLICKERFREE DIM IP54 3K/3.5K/4K BEAM60D DEESET BLACK	12	1020	3000/ 3500/ 4000	60	85	90	96	92
LDLP20WBK	4099854514319	VILLAGLOW DOWNLIGHT TC 20W 2000LM CRI90 C0120MM UGR19 SDCM3 IC-4 FLICKERFREE DIM IP54 3K/3.5K/4K BEAM60D DEESET BLACK	20	2000	3000/ 3500/ 4000	60	100	120	130	98

*Denotes of Model Number: L-LEDVANCE; 9/12/20W-9/12/20 Watts; WH-White; BK-Black

1 The Rated Lumen outputs are specified @3500K/4000K. Lumen outputs @3000K is 8% less than the above rated lumen outputs respectively.