

# PRODUCT DATASHEET

## HE ES 25 W/830

LUMILUX T5 HE ES | Tubular fluorescent lamps 16 mm, high efficiency, energy saver, with G5 base



---

### AREAS OF APPLICATION

- Public buildings
- Offices
- Shops
- Supermarkets and department stores
- Industry
- Outdoor applications only in suitable luminaires

---

### PRODUCT BENEFITS

- Up to 10 % energy savings compared to standard T5 HE LUMILUX lamps
- Excellent economy and efficiency
- Pay-back time less than 1 year
- High luminous efficacy

---

### PRODUCT FEATURES

- Luminous efficacy: up to 114 lm/W
- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Long average lifetime: up to 24,000 h (with QUICKTRONIC ECG)
- Good color rendering group: 1B ( $R_a$ : 80...89)
- Dimmable



**TECHNICAL DATA**

Electrical data

Nominal voltage	143 V
Rated lamp efficacy (HF data 25 °C)	97 lm/W
Rated wattage	25.30 W
Nominal wattage	32.00 W

Photometrical data

Color rendering index Ra	≥80
Rated luminous flux	2450 lm
Luminous flux at 25 °C	2450 lm
Luminous flux at 35 °C	2900 lm
Light color	830
Rated color temperature	3000 K
Nominal luminous flux	2450 lm
Light color (designation)	LUMILUX Warm White
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.93
Rated LLMF at 6,000 h	0.92
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Color temperature	3000 K
Luminous flux	2450 lm
Color rendering index Ra	≥80

Dimensions & weight



Tube diameter	16 mm
---------------	-------

<b>Length</b>	1149 mm
<b>Length with base excl. base pins/connection</b>	1149.00 mm
<b>Diameter</b>	16.0 mm

### Temperatures & operating conditions

<b>Rated ambient temp.w.max.luminous flux</b>	35.0 °C
---	---------

### Lifespan

<b>Service life</b>	19000 h <sup>1)</sup>
<b>Lifespan</b>	24000 h <sup>1)</sup>
<b>Rated lamp survival factor at 2,000 h</b>	0.99
<b>Rated lamp survival factor at 4,000 h</b>	0.99
<b>Rated lamp survival factor at 6,000 h</b>	0.99
<b>Rated lamp survival factor at 8,000 h</b>	0.99
<b>Rated lamp survival factor at 12,000 h</b>	0.99
<b>Rated lamp survival factor at 16,000 h</b>	0.97
<b>Rated lamp survival factor at 20,000 h</b>	0.85
<b>Operation mode LLMF/LSF</b>	HF
<b>Rated lamp life time</b>	24000 h
<b>Nominal lamp life time</b>	24000 h

<sup>1)</sup> With preheat ECG

### Additional product data

<b>Base (standard designation)</b>	G5
<b>Mercury content</b>	1.7 mg
<b>Show WEEE picto</b>	Yes
<b>Product remark</b>	For ECG operation only/Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C

### Capabilities

<b>Dimmable</b>	Yes
<b>Suitable for indoor</b>	Yes

### Certificates & standards

<b>Energy efficiency class</b>	A+
<b>Energy consumption</b>	28 kWh/1000h

Light Distribution



Spectral power distribution

Wiring Diagram



Wiring diagram



Wiring diagram

---

**SYSTEM GUARANTEE**

OSRAM System+ Guarantee in combination with OSRAM ECGs

---

**SAFETY ADVICE**

In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

---

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321957894	Sleeves 1	1170 mm x 22 mm x 22 mm	127.00 g	0.57 dm <sup>3</sup>
4008321958051	Shipping carton box 20	1182 mm x 83 mm x 104 mm	2712.50 g	10.20 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**REFERENCES / LINKS**

For more information on the system guarantee and the terms and conditions of the guarantee visit

▶ [www.ledvance.com/system-guarantee](http://www.ledvance.com/system-guarantee)

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

## LUMILUX T5 HE ES | Tubular fluorescent lamps 16 mm, high efficiency, energy saver, with G5 base

Product name	Product name ECG	EAN	Nominal current	Nominal wattage + Power loss	Luminous flux at 35 °C	Number of lighting outlets
HE ES 25 W/830	QT-FIT 5 1x14-35	4008321971234	0.12 A	28.00 W	2450 lm	1
	QT-FIT 5 2x14-35	4008321971258	0.25 A	56.00 W	2450 lm	2
	QTi 1x14/24/21/39 GII	4008321383334	0.13 A	29.00 W	2500 lm	1
	QTi 1x28/54/35/49 GII	4008321383358	0.13 A	29.00 W	2500 lm	1
	QTi 2x14/24/21/39 GII	4008321383396	0.26 A	56.00 W	2500 lm	2
	QTi 2x35/49/80 GII	4008321658951	0.26 A	57.00 W	2500 lm	2
	QTP5 1x14-35	4008321329035	0.12 A	27.00 W	2450 lm	1
	QTP5 2x14-35	4008321329073	0.24 A	54.00 W	2450 lm	2