

PRODUCT DATASHEET

HCI-TS 70 W/830 WDL PB

POWERBALL HCI-TS | Metal halide lamps with ceramic technology for enclosed luminaires



AREAS OF APPLICATION

- Shopping arcades
- Foyers, reception areas
- Museums, exhibitions
- Exhibition halls and trade fairs
- Factories and workshops
- Buildings, monuments, bridges
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Very high efficiency
- Good to excellent color rendering
- Very good color stability
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

PRODUCT FEATURES

- POWERBALL ceramic technology
- Average lifetime: 15,000 h (operation with ECG with 70...400 Hz square-wave current)
- Average lifetime: 12,000 h (with magnetic control gear)



TECHNICAL DATA

Electrical data

Rated wattage	73.00 W
Lamp current	0.95 A
PFC capacitor at 50 Hz	12 µF ¹⁾
Nominal wattage	70.00 W
Ignition voltage	3.6 / 4.5 kVp ²⁾

¹⁾ At rated voltage and $\cos \varphi \geq 0.9$


²⁾ Minimum; for superimposed ignition with square wave electronic ballast 3.0 kVp are sufficient / Maximum; this limit is for safety reasons

Photometrical data

Luminous flux	7000 lm
Luminous efficacy	97 lm/W ¹⁾
Color rendering index Ra	88
Color temperature	3000 K
Light color	831
Rated LLMF at 2,000 h	0.84
Rated LLMF at 4,000 h	0.82
Rated LLMF at 6,000 h	0.79
Rated LLMF at 8,000 h	0.76
Rated LLMF at 12,000 h	0.71
UV protection	Yes
Color temperature	3100 K

¹⁾ In operation with low frequency square wave electronic ballast, 70...400 Hz. Operation with electromagnetic ballast may be less efficient.

Dimensions & weight



Diameter	20.0 mm
Length	120.0 mm
Light center length (LCL)	60.0 mm
Product weight	20.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	500 °C
Maximum permitted pinch temperature	330 °C

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.98
Rated lamp survival factor at 6,000 h	0.97
Rated lamp survival factor at 8,000 h	0.96
Rated lamp survival factor at 12,000 h	0.80
Lifespan B50	15000 h ¹⁾
Operation mode LLMF/LSF	ECG

¹⁾ At ECG

Additional product data

Base (standard designation)	RX7s
System guarantee level	3 (2/5)
Mercury content	5.5 mg ¹⁾

¹⁾ Maximum

Capabilities

Dimmable	Yes ¹⁾
Burning position	p45
Enclosed luminaire required	Yes

¹⁾ In combination with POWERTRONIC PTo


Certificates & standards

Energy efficiency class	A+
Energy consumption	81 kWh/1000h

Country-specific categorizations

ILCOS	MD/UB-70/830-H/SL-RX7s-22/114,2/H
-------	-----------------------------------

Light Distribution



Spectral power distribution

SYSTEM GUARANTEE

- When operated with OSRAM POWERTRONIC control gear, an extended system guarantee is granted for these lamps

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321688309	Folding carton box 1	142 mm x 42 mm x 42 mm	34.00 g	0.25 dm ³
4008321688316	Shipping carton box 12	180 mm x 161 mm x 139 mm	490.00 g	4.03 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For more information on the system guarantee and the terms and conditions of the guarantee visit

- ▶ www.ledvance.com/system-guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

POWERBALL HCI-TS | Metal halide lamps with ceramic technology for enclosed luminaires