

# PRODUCT DATASHEET

## P PIN 10 0.9 W/2700K G4

PARATHOM LED PIN G4 12 V | Low-voltage 12 V LED lamps with retrofit pin base G4



---

### AREAS OF APPLICATION

- Atmospheric accent lighting throughout the home
- Shops, hotels and restaurants
- Foyers, offices
- Outdoor applications only in suitable luminaires

---

### PRODUCT BENEFITS

- Long lifetime of up to 15,000 h
- Low energy consumption
- Ideal for decorative and free-burning applications

---

### PRODUCT FEATURES

- LED alternative to conventional low voltage lamps
- Mercury-free lamps



**TECHNICAL DATA**

Electrical data

<b>Rated wattage</b>	0.90 W
<b>Nominal wattage</b>	0.90 W
<b>Nominal voltage</b>	12 V
<b>Power factor <math>\lambda</math></b>	0.50
<b>Claimed equiv. conventional lamp power</b>	10 W


Photometrical data

<b>Nominal luminous flux</b>	100 lm
<b>Rated luminous flux</b>	100 lm
<b>Lumen main.fact.at end of nom.life time</b>	0.70
<b>Light color (designation)</b>	Warm White
<b>Color temperature</b>	2700 K
<b>Luminous flux</b>	100 lm
<b>Color rendering index Ra</b>	$\geq 80$
<b>Standard deviation of color matching</b>	$\leq 6$ sdc <sub>m</sub>
<b>Rated color temperature</b>	2700 K
<b>Color rendering index Ra</b>	$\geq 80$

Light technical data

<b>Warm-up time (60 %)</b>	< 0.50 s
<b>Beam angle</b>	300.00 °
<b>Starting time</b>	< 0.5 s

Dimensions & weight



<b>Overall length</b>	33.0 mm
<b>Diameter</b>	12.0 mm
<b>Outer bulb</b>	T12

<b>Length</b>	33.0 mm
---------------	---------

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+40 °C
<b>Maximum temperature at tc test point</b>	88 °C

### Lifespan

<b>Nominal lamp life time</b>	15000 h
<b>Rated lamp life time</b>	15000 h
<b>Number of switching cycles</b>	100000
<b>Lumen maintenance at end of service life</b>	0.70

### Additional product data

<b>Base (standard designation)</b>	G4
<b>Mercury content</b>	0.0 mg
<b>Mercury-free</b>	Yes
<b>Design / version</b>	Clear
<b>Show WEEE picto</b>	Yes

### Capabilities

<b>Dimmable</b>	No
-----------------	----

### Certificates & standards

<b>Energy efficiency class</b>	A++
<b>Energy consumption</b>	1 kWh/1000h

### Country-specific categorizations

<b>ILCOS</b>	DRT/C-0,9/827-220-240-G4-12/33
<b>Order reference</b>	LEDPPIN10 CL 0,

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075811959	Folding carton box 1	28 mm x 28 mm x 67 mm	7.40 g	0.05 dm <sup>3</sup>
4058075811966	Shipping carton box 20	150 mm x 122 mm x 77 mm	206.00 g	1.41 dm <sup>3</sup>
4058075042438	Shipping carton box 120	256 mm x 160 mm x 248 mm	1371.00 g	10.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**REFERENCES / LINKS**

For further products and actual information concerning LED lamps see

- ▶ [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.