

## PRODUCT DATASHEET OT Programmer

OT Programmer | USB Programming interface



---

### PRODUCT FAMILY FEATURES

- Standard USB interface
- Very fast programming of single OPTOTRONIC devices with the Prog +/- interface
- Programming without applying mains voltage to the driver
- Suitable only for non-DALI OPTOTRONIC devices with the Prog +/- interface

**TECHNICAL DATA**

## Electrical data

<b>Nominal voltage</b>	5 V
<b>Mains frequency</b>	0 Hz

## Dimensions &amp; weight

<b>Length</b>	120.0 mm
<b>Width</b>	76.0 mm
<b>Height</b>	28.0 mm
<b>Product weight</b>	200.00 g

## Colors &amp; materials

<b>Product color</b>	Grey
----------------------	------

## Temperatures &amp; operating conditions

<b>Ambient temperature range</b>	0...+50 °C
----------------------------------	------------

## Capabilities

<b>Dimmable</b>	No
-----------------	----

## Certificates &amp; standards

<b>Type of protection</b>	IP20
---------------------------	------



## Logistical data

<b>Temperature range at storage</b>	-25...80 °C
-------------------------------------	-------------

**EQUIPMENT / ACCESSORIES**

– Programmable via Tuner4TRONIC software

**DOWNLOAD DATA**

File
 Declarations of conformity 642506_OT Programmer EC-Declaration of Conformity
 Declarations of conformity 643182_EC Conformity OT Programmer

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899209640	Unpacked 1	- x - x -		
4052899209657	Shipping carton box 1	210 mm x 133 mm x 89 mm	289.00 g	2.49 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.