

PRODUCT DATASHEET

LED T8 Starter

SubstiTUBE Start | Starter for SubstiTUBE EM (CCG)



AREAS OF APPLICATION

- Not suitable for operation with electronic control gears

PRODUCT BENEFITS

- Extremely break resistant thanks to cover made of polycarbonate
- Mercury-free and RoHS compliant

PRODUCT FEATURES

- Substitute starter for the replacement of a fluorescent lamp with a LED tube
- Suitable for operation with low loss or conventional control gear or line voltage
- Integrated electrical fuse




TECHNICAL DATA

Electrical data

Operating frequency	-
----------------------------	---

Dimensions & weight



Product weight	5.00 g
-----------------------	--------

Country-specific categorizations

Order reference	SUBSTITUTE LED
------------------------	----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075013674	Folding carton box 2	46 mm x 25 mm x 42 mm	14.00 g	0.05 dm ³
4058075013681	Shipping carton box 20	99 mm x 32 mm x 218 mm	169.00 g	0.69 dm ³
4058075013698	Shipping carton box 840	446 mm x 309 mm x 246 mm	7.42 g	33.90 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.