

# PRODUCT DATASHEET

## SST CLAS BA 40 4.5 W/2700K E14

LED SUPERSTAR CLASSIC BA GLOWdim | LED lamps with GLOWdim effect, classic candle shape



### AREAS OF APPLICATION

- Hospitality
- Historical buildings
- Residential interiors
- Marine lighting
- Outdoor applications only in suitable luminaires

### PRODUCT BENEFITS

- Provides an especially warm light when dimmed down
- Directly controllable via standard dimmer, no remote control required
- Can be easily combined with other GLOWdim products in one application
- Very long lifetime of up to 25,000 h
- Low energy consumption
- Easy relamping thanks to compact design

### PRODUCT FEATURES

- LED alternative to conventional lamps
- Dimming changes light color from warm white (2,700 K) to extra warm white (2,000 K)
- Good quality of light; color rendering index  $R_a \geq 80$
- Dimmable (with many common dimmers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim))
- Mercury-free lamps



**TECHNICAL DATA**


Electrical data

<b>Rated wattage</b>	4.50 W
<b>Nominal wattage</b>	4.50 W
<b>Nominal voltage</b>	220...240 V
<b>Operating frequency</b>	50...60 Hz

Photometrical data

<b>Lumen main.fact.at end of nom.life time</b>	0.70
<b>Light color (designation)</b>	Tunable Warm White
<b>Color temperature</b>	2700 K
<b>Luminous flux</b>	470 lm
<b>Color rendering index Ra</b>	≥80
<b>Adjustable color temperature</b>	2200...2700 K
<b>Nominal luminous flux</b>	470 lm
<b>Rated color temperature</b>	2700 K

Dimensions & weight



<b>Overall length</b>	141.0 mm
-----------------------	----------

Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+40 °C
<b>Maximum temperature at tc test point</b>	65 °C

Lifespan

<b>Nominal lamp life time</b>	15000 h
<b>Rated lamp life time</b>	15000 h
<b>Number of switching cycles</b>	100000

## Additional product data

<b>Base (standard designation)</b>	E14
<b>Mercury-free</b>	Yes
<b>Product remark</b>	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

## Capabilities

<b>Dimmable</b>	Yes
-----------------	-----

## Certificates &amp; standards

<b>Energy efficiency class</b>	A++
--------------------------------	-----

## Country-specific categorizations

<b>ILCOS</b>	DRBB/C-5-827-220-240-E14-35
<b>Order reference</b>	LEDSCBA40GD4,5W

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075809024	Blister 1	42 mm x 140 mm x 120 mm	47.00 g	0.71 dm <sup>3</sup>
4058075810457	Shipping carton box 6	261 mm x 153 mm x 136 mm	359.00 g	5.43 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.