

# PRODUCT DATASHEET

## ST CLAS A 60 FR 9 W/2700K E27

LED Retrofit RGBW lamps with remote control | Consumer LED RGBW lamps with remote control



---

### AREAS OF APPLICATION

- Domestic applications

---

### PRODUCT BENEFITS

- Easy installation
- Up to 80 % less energy consumption compared with ordinary light bulbs
- Individual control
- No app or smartphone required to control the lamp
- Comfortable and intuitive infrared remote control
- Switching, dimming in 4 steps and color control with the push of a button
- Color loops for dynamic color changes

---

### PRODUCT FEATURES

- Lifetime: up to 25,000 h
- Allows for control of colors, saturation and dimming levels
- Wide range of controllable light colors including white
- Four dynamic effects: Flash, Strobe, Smooth, Mode



## TECHNICAL DATA


### Electrical data

Rated wattage	9.00 W
Nominal wattage	9.00 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	130
Max. lamp no. on circuit break. 16 A (B)	110
Operating frequency	50...60 Hz

### Photometrical data

Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	806 lm
Color rendering index Ra	≥80
Nominal luminous flux	806 lm
Rated color temperature	2700 K

### Dimensions & weight



Overall length	114.0 mm
----------------	----------

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	80 °C

### Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000

## Additional product data

<b>Base (standard designation)</b>	E27
<b>Mercury-free</b>	Yes
<b>Product remark</b>	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

## Capabilities

<b>Dimmable</b>	No
-----------------	----

## Certificates &amp; standards

<b>Energy efficiency class</b>	A+
--------------------------------	----

## Country-specific categorizations

<b>Order reference</b>	LEDSCLA60REM 9W
------------------------	-----------------

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075045675	Blister 1	67 mm x 140 mm x 185 mm	80.00 g	1.74 dm <sup>3</sup>
4058075045682	Shipping carton box 6	416 mm x 153 mm x 201 mm	777.00 g	12.79 dm <sup>3</sup>
4058075091733	Blister 2	67 mm x 140 mm x 240 mm	153.00 g	2.25 dm <sup>3</sup>
4058075091740	Shipping carton box 12	416 mm x 153 mm x 256 mm	1143.00 g	16.29 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.