

PRODUCT DATASHEET DALI ACU BT

DALI ACU BT | Control units for light management systems



AREAS OF APPLICATION

- Offices
- Conference rooms
- Training rooms
- Shop lighting

PRODUCT FAMILY BENEFITS

- Control of standard white or Tunable White light acc. DALI device type 8 (DT8)*
- Intuitive manual dimming and switching
- Basic functionality without configuration thanks to applied pre-settings
- Up to 4 groups separately controllable
- Integrated DALI supply
- Simple creation of scenes via App

PRODUCT FAMILY FEATURES


- Light control with app connection via Bluetooth
- One DALI output channel (Broadcast or Groupcast)
- Operation via standard pushbutton
- Combinable with OSRAM DALI presence- and motion detectors
- Length of the DALI control cable: up to 300 m
- Length of the pushbutton cable: up to 50m

TECHNICAL DATA

Electrical data

System wattage [AGGR]	3.00 W
------------------------------	--------

Dimensions & weight



Width	48.0 mm
Height	22.0 mm
Product weight	40.00 g

Capabilities

Number of control outputs	1
----------------------------------	---




Certificates & standards

Protection class	II
-------------------------	----

EQUIPMENT / ACCESSORIES

- Suitable for up to 32 electronic control gears
- Free App for iOS and Android available at the app store

DOWNLOAD DATA

File	
	User instruction DALI ACU BT Control
	User instruction DALI ACU BT Control
	Declarations of conformity EU Declaration of Conformity DALI ACU BT

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899544826	Shipping carton box 60	344 mm x 254 mm x 278 mm	3847.00 g	24.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.