

PRODUCT DATASHEET

ENDURA CLASSIC Wall E27 BK

ENDURA CLASSIC WALL | Wall luminaire with direct light



AREAS OF APPLICATION

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies

PRODUCT BENEFITS

- High flexibility in the choice of the light source thanks to E27 base
- Suitable for smart applications thanks to compatibility with Smart + lamps from LEDVANCE
- Easy and quick installation

PRODUCT FEATURES

- Die-cast aluminum housing
- Diffuser made of semi-transparent polycarbonate




TECHNICAL DATA

Electrical data

Operating mode	Mains voltage
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Dimensions & weight



Length	126.0 mm
Width	156.0 mm
Height	220.0 mm
Product weight	1220.00 g

Colors & materials

Body material	Aluminum
Product color	Black
Housing color	Black
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
----------------------------------	--------------

Additional product data

Mounting type	Surface
Mounting location	Wall
Equipped with lamp	No

Capabilities

Dimmable	No
Type of connection	Screw terminal

Holder designation	E27
---------------------------	-----

Certificates & standards

Protection class	I
Type of protection	IP44
Standards	CE/EAC/REACH/RoHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075206120	Folding carton box 1	134 mm x 204 mm x 236 mm	1287.00 g	6.45 dm ³
4058075206137	Shipping carton box 4	549 mm x 214 mm x 250 mm	5490.00 g	29.37 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.