

# PRODUCT DATASHEET

## LED Switch Batten 300 mm 4 W 3000 K

**LED SWITCH BATTEN | Slim LED batten luminaires with included switch, joinable for seamless strip lighting**



---

### AREAS OF APPLICATION

- Indoor applications
- Under cabinet lighting
- Accent lighting
- General indoor illumination
- Corridors, entrance areas, stairwells, living rooms, basements
- Cove lighting

---

### PRODUCT BENEFITS

- Little space required thanks to compact dimensions
- Ready for connection due to integrated on/off switch and cable with EU-plug
- Easy and quick electrical connection for light line installation
- Flexible application due to a wide range of available lengths of 300 to 1200 mm.
- Flexible installation in 2 different angles with 2 different mounting options

---

### PRODUCT FEATURES

- Replacement for traditional T8 luminaires
- On/off switch on luminaire
- Polycarbonate housing
- Lifetime: up to 30,000 h
- Color temperature: 3,000 K, 4,000 K
- High luminous efficacy: up to 115 lm/W
- Lengths available: 0.3 m, 0.6 m, 0.9 m, 1.2 m



- Mounting accessories included

**TECHNICAL DATA**

Electrical data

<b>Nominal wattage</b>	4.00 W
<b>Operating mode</b>	Mains voltage
<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz

Photometrical data

<b>Color temperature</b>	3000 K
<b>Color rendering index Ra</b>	≥80
<b>Light color (designation)</b>	Warm White
<b>Luminous flux</b>	450 lm
<b>Luminous efficacy</b>	110 lm/W

Light technical data

<b>Beam angle</b>	140 °
-------------------	-------

Dimensions & weight



<b>Length</b>	313.0 mm
<b>Width</b>	22.0 mm
<b>Height</b>	30.0 mm
<b>Product weight</b>	188.00 g
<b>Cable length</b>	1500 mm

Colors & materials

<b>Body material</b>	Polycarbonate (PC)
<b>Product color</b>	White
<b>Housing color</b>	White

<b>Cover material</b>	Polycarbonate (PC)
-----------------------	--------------------

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+40 °C
<b>Temperature range in operation</b>	-20...+40 °C

### Lifespan

<b>Number of switching cycles</b>	25000
<b>Rated lamp life time</b>	30000 h

### Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Ceiling
<b>Mercury content</b>	0.0 mg

### Capabilities

<b>Dimmable</b>	No
<b>Type of connection</b>	Plug type C (EU)
<b>LED module replaceable</b>	Not replaceable

### Certificates & standards

<b>Protection class</b>	II
<b>Type of protection</b>	IP20
<b>Standards</b>	CE/EAC/REACH/RoHS
<b>ErP For end-consumer</b>	yes
<b>EEL of included LED module</b>	A++/A+/A

### Logistical data

<b>ErP For end-consumer</b>	yes
-----------------------------	-----

## EQUIPMENT / ACCESSORIES

- Equipped with 1.5 m cable and EU plug
- Mounting bracket included
- Fixed connector and flexible connecting cable included

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075266681	Folding carton box 1	41 mm x 46 mm x 406 mm	242.00 g	0.77 dm <sup>3</sup>

---

4058075266698	Shipping carton box 8	416 mm x 205 mm x 105 mm	2122.00 g	8.95 dm <sup>3</sup>
---------------	--------------------------	--------------------------	-----------	----------------------

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.