

PRODUCT FAMILY DATASHEET

LED SWITCH BATTEN

Slim LED batten luminaires with included switch, joinable for seamless strip lighting



AREAS OF APPLICATION

- Indoor applications
- Under cabinet lighting
- Accent lighting
- General indoor illumination
- Corridors, entrance areas, stairwells, living rooms, basements
- Cove lighting

PRODUCT BENEFITS

- Little space required thanks to compact dimensions
- Ready for connection due to integrated on/off switch and cable with EU-plug
- Easy and quick electrical connection for light line installation
- Flexible application due to a wide range of available lengths of 300 to 1200 mm.
- Flexible installation in 2 different angles with 2 different mounting options

PRODUCT FEATURES

- Replacement for traditional T8 luminaires
- On/off switch on luminaire
- Polycarbonate housing
- Lifetime: up to 30,000 h
- Color temperature: 3,000 K, 4,000 K
- High luminous efficacy: up to 115 lm/W
- Lengths available: 0.3 m, 0.6 m, 0.9 m, 1.2 m



- Mounting accessories included


TECHNICAL DATA

Product description	Electrical data			Photometrical data		Light technical data	Dimensions & weight				Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Beam angle	Length	Width	Height	Product weight	Body material
LED Switch Batten 300 mm 4 W 3000 K	4.00 W	220...240 V	50/60 Hz	3000 K	450 lm	140 °	313.0 mm	22.0 mm	30.0 mm	188.00 g	Polycarbonate (PC)
LED Switch Batten 300 mm 4 W 4000 K	4.00 W	220...240 V	50/60 Hz	4000 K	450 lm	140 °	313.0 mm	22.0 mm	30.0 mm	188.00 g	Polycarbonate (PC)
LED Switch Batten 600 mm 8 W 3000 K	8.00 W	220...240 V	50/60 Hz	3000 K	900 lm	140 °	573.0 mm	22.0 mm	30.0 mm	227.00 g	Polycarbonate (PC)
LED Switch Batten 600 mm 8 W 4000 K	8.00 W	220...240 V	50/60 Hz	4000 K	900 lm	140 °	573.0 mm	22.0 mm	30.0 mm	227.00 g	Polycarbonate (PC)
LED Switch Batten 900 mm 10 W 3000 K	10.00 W	220...240 V	50/60 Hz	3000 K	1100 lm	140 °	873.0 mm	22.0 mm	30.0 mm	263.00 g	Polycarbonate (PC)
LED Switch Batten 900 mm 10 W 4000 K	10.00 W	220...240 V	50/60 Hz	4000 K	1100 lm	140 °	873.0 mm	22.0 mm	30.0 mm	263.00 g	Polycarbonate (PC)
LED Switch Batten 1200 mm 14 W 3000 K	14.00 W	220...240 V	50/60 Hz	3000 K	1600 lm	140 °	1173 mm	22.0 mm	30.0 mm	304.00 g	Polycarbonate (PC)
LED Switch Batten 1200 mm 14 W 4000 K	14.00 W	220...240 V	50/60 Hz	4000 K	1600 lm	140 °	1173 mm	22.0 mm	30.0 mm	304.00 g	Polycarbonate (PC)

Product description	Product color	Housing color	Cover material	Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
				Ambient temperature range	Number of switching cycles	Dimmable	Type of connection	Protection class	Type of protection
LED Switch Batten 300 mm 4 W 3000 K	White	White	Polycarbonate (PC)	-20...+40 °C	25000	No	Plug type C (EU)	II	IP20
LED Switch Batten 300 mm 4 W 4000 K	White	White	Polycarbonate (PC)	-20...+40 °C	25000	No	Plug type C (EU)	II	IP20
LED Switch Batten 600 mm 8 W 3000 K	White	White	Polycarbonate (PC)	-20...+40 °C	25000	No	Plug type C (EU)	II	IP20

Product description	Product color	Housing color	Cover material	Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
				Ambient temperature range	Number of switching cycles	Dimmable	Type of connection	Protection class	Type of protection
LED Switch Batten 600 mm 8 W 4000 K	White	White	Polycarbonate (PC)	-20...+40 °C	25000	No	Plug type C (EU)	II	IP20
LED Switch Batten 900 mm 10 W 3000 K	White	White	Polycarbonate (PC)	-20...+40 °C	25000	No	Plug type C (EU)	II	IP20
LED Switch Batten 900 mm 10 W 4000 K	White	White	Polycarbonate (PC)	-20...+40 °C	25000	No	Plug type C (EU)	II	IP20
LED Switch Batten 1200 mm 14 W 3000 K	White	White	Polycarbonate (PC)	-20...+40 °C	25000	No	Plug type C (EU)	II	IP20
LED Switch Batten 1200 mm 14 W 4000 K	White	White	Polycarbonate (PC)	-20...+40 °C	25000	No	Plug type C (EU)	II	IP20

Product description	Logistical data	
	ErP For end-consumer	
LED Switch Batten 300 mm 4 W 3000 K	yes	
LED Switch Batten 300 mm 4 W 4000 K	yes	
LED Switch Batten 600 mm 8 W 3000 K	yes	
LED Switch Batten 600 mm 8 W 4000 K	yes	
LED Switch Batten 900 mm 10 W 3000 K	yes	
LED Switch Batten 900 mm 10 W 4000 K	yes	
LED Switch Batten 1200 mm 14 W 3000 K	yes	
LED Switch Batten 1200 mm 14 W 4000 K	yes	



LED Switch Batten 300 mm 4 W 3000 K,
LED Switch Batten 300 mm 4 W 4000 K

LED Switch Batten 600 mm 8 W 3000 K,
LED Switch Batten 600 mm 8 W 4000 K

LED Switch Batten 900 mm 10 W 3000
K, LED Switch Batten 900 mm 10 W
4000 K

LED Switch Batten 1200 mm 14 W 3000
K, LED Switch Batten 1200 mm 14 W
4000 K

EQUIPMENT / ACCESSORIES

- Equipped with 1.5 m cable and EU plug
- Mounting bracket included
- Fixed connector and flexible connecting cable included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075266698	Shipping carton box 8	416 mm x 205 mm x 105 mm	2122.00 g	8.95 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075266711	Shipping carton box 8	416 mm x 205 mm x 105 mm	2122.00 g	8.95 dm ³
4058075266735	Shipping carton box 8	645 mm x 205 mm x 105 mm	2667.00 g	13.88 dm ³
4058075266759	Shipping carton box 8	645 mm x 205 mm x 105 mm	2667.00 g	13.88 dm ³
4058075266872	Shipping carton box 8	930 mm x 205 mm x 105 mm	3131.00 g	20.02 dm ³
4058075266971	Shipping carton box 8	930 mm x 205 mm x 105 mm	3131.00 g	20.02 dm ³
4058075266995	Shipping carton box 8	1245 mm x 205 mm x 105 mm	3717.00 g	26.80 dm ³
4058075267053	Shipping carton box 8	1245 mm x 205 mm x 105 mm	3717.00 g	26.80 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.