

# PRODUCT FAMILY DATASHEET

## Slim design

Slim LED luminaires with LED module



---

### AREAS OF APPLICATION

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Kitchens, workspaces

---

### PRODUCT BENEFITS

- Very slim design
- Energy savings of up to 80 % compared to luminaires using conventional lamps
- Easy and quick installation

---

### PRODUCT FEATURES

- Ceiling luminaire with advanced LED technology
- Circular light emission




**TECHNICAL DATA**

Product description	Electrical data			Photometrical data		Light technical data	Dimensions & weight			Colors & materials	
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Beam angle	Diameter	Height	Product weight	Body material	Housing color
LED FLAT 20 W 2700 K	20.00 W	220...240 V	50/60 Hz	2700 K	1200 lm	180 °	380.0 mm	29.0 mm	710.00 g	Polycarbonate (PC)	Gray
LED RING 18 W 2700 K	18.00 W	220...240 V	50/60 Hz	2700 K	1200 lm	180 °	280.0 mm	29.0 mm	415.00 g	Polycarbonate (PC)	Gray


Product description	Product color	Cover material	Temperatures & operating conditions	Lifespan	Lifespan	Capabilities		Certificates & standards
			Ambient temperature range	Number of switching cycles		Dimmable	Type of connection	Protection class
LED FLAT 20 W 2700 K	Gray	Polycarbonate (PC)	-20...+40 °C	50000	20000 h	No	Screw terminal	II
LED RING 18 W 2700 K	Gray	Polycarbonate (PC)	0...+40 °C	50000	20000 h	No	Screw terminal	II

Product description	Type of protection
LED FLAT 20 W 2700 K	IP20
LED RING 18 W 2700 K	IP20



---

Product line drawing



---

Product line drawing

---

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

---

### APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

---

### DISCLAIMER

- Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.