

PRODUCT FAMILY DATASHEET

LinearLED Flat

Slim undercabinet luminaire for surface mounting

AREAS OF APPLICATION

- Undercabinet lighting



PRODUCT BENEFITS

- Connection of up to 43 (ECO version) or 18 (sensor Version) luminaires in a row
- Various accessories included: cables and connectors




TECHNICAL DATA

Product description	Electrical data			Photometrical data		Light technical data	Dimensions & weight				Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Beam angle	Length	Width	Height	Product weight	Body material
Linear LED Flat 6 W 3000 K	6.00 W	220...240 V	50/60 Hz	3000 K	300 lm	120 °	370.0 mm	67.0 mm	22.0 mm	325.00 g	Aluminum
Linear LED Flat 12 W 3000 K	12.00 W	220...240 V	50/60 Hz	3000 K	760 lm	120 °	527.0 mm	67.0 mm	19.0 mm	425.00 g	Aluminum
Linear LED Flat 6 W 4000 K	6.00 W	220...240 V	50/60 Hz	4000 K	320 lm	120 °	370.0 mm	67.0 mm	22.0 mm	325.00 g	Aluminum
Linear LED Flat 12 W 4000 K	12.00 W	220...240 V	50/60 Hz	4000 K	840 lm	120 °	527.0 mm	67.0 mm	19.0 mm	425.00 g	Aluminum

Product description	Product color	Housing color	Cover material	Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
				Ambient temperature range	Number of switching cycles	Dimmable	Type of connection	Protection class	Type of protection
Linear LED Flat 6 W 3000 K	Silver	Silver	Polycarbonate (PC)	-20...+40 °C	100000	No	Plug, EU	II	IP20
Linear LED Flat 12 W 3000 K	Silver	Silver	Polycarbonate (PC)	-20...+40 °C	100000	No	Plug, EU	II	IP20
Linear LED Flat 6 W 4000 K	Silver	Silver	Polycarbonate (PC)	-20...+40 °C	100000	No	Plug, EU	II	IP20
Linear LED Flat 12 W 4000 K	Silver	Silver	Polycarbonate (PC)	-20...+40 °C	100000	No	Plug, EU	II	IP20

Product description	Logistical data
	ErP For end-consumer
Linear LED Flat 6 W 3000 K	yes
Linear LED Flat 12 W 3000 K	yes
Linear LED Flat 6 W 4000 K	yes
Linear LED Flat 12 W 4000 K	yes



Linear LED Flat 6 W 3000 K, Linear LED Flat 6 W 4000 K

Linear LED Flat 12 W 3000 K, Linear LED Flat 12 W 4000 K

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075264151	Shipping carton box 8	422 mm x 334 mm x 83 mm	3706.00 g	11.70 dm ³
4058075264427	Shipping carton box 8	651 mm x 334 mm x 83 mm	4809.00 g	18.05 dm ³
4058075264335	Shipping carton box 8	422 mm x 334 mm x 83 mm	3806.00 g	11.70 dm ³
4058075264625	Shipping carton box 8	651 mm x 334 mm x 83 mm	4860.00 g	18.05 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
--------------	------------------------------	--------------------------------------	--------------	--------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.