

# PRODUCT DATASHEET

## LED Office Line Grid DIM 600 mm 25 W 4000 K

**LED OFFICE LINE GRID DIM | Dimmable luminaire for ceiling and pendant mounting with a grid for glare reduction**

---

### AREAS OF APPLICATION

- Indoor applications
- Home offices
- General indoor illumination
- Kitchens, workspaces



---

### PRODUCT BENEFITS

- Energy savings thanks to dimming in three steps
- Flexible mounting options
- Functional and minimalistic design

---

### PRODUCT FEATURES

- Replacement for traditional T8 luminaires
- For ceiling mounting or pendant mounting
- Material: Aluminium (Housing), Polycarbonate (Diffusor)
- Lifetime: up to 25,000 h
- Click-DIM version: dimmable in three steps by repeated switching
- GRID Version with included louver grid
- Lengths available: 0.6 m, 1.2 m
- Color temperature: 4,000 K



**TECHNICAL DATA**

Electrical data

<b>Nominal wattage</b>	25.00 W
<b>Operating mode</b>	Mains voltage
<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz


Photometrical data

<b>Color temperature</b>	4000 K
<b>Color rendering index Ra</b>	≥80
<b>Light color (designation)</b>	Cool White
<b>Luminous flux</b>	2000 lm
<b>Luminous efficacy</b>	80 lm/W

Light technical data

<b>Beam angle</b>	105.00 °
-------------------	----------

Dimensions & weight



<b>Length</b>	595.0 mm
<b>Width</b>	134.0 mm
<b>Height</b>	46.0 mm
<b>Product weight</b>	827.00 g

Colors & materials

<b>Body material</b>	Aluminum
<b>Product color</b>	White
<b>Housing color</b>	White

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Temperature range in operation	-20...+40 °C

### Lifespan

Number of switching cycles	25000
Rated lamp life time	25000 h

### Additional product data

Mounting type	Surface
Mounting location	Ceiling
Mercury content	0.0 mg

### Capabilities

Dimmable	Yes
Type of connection	Screw terminal
LED module replaceable	Not replaceable

### Certificates & standards

Protection class	I
Type of protection	IP20
Standards	CE/EAC/REACH/RoHS
ErP For end-consumer	yes
EEL of included LED module	A++/A+/A

### Logistical data

ErP For end-consumer	yes
----------------------	-----

## EQUIPMENT / ACCESSORIES

- Pendant mounting accessory included

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075271548	Folding carton box 1	51 mm x 141 mm x 771 mm	924.00 g	5.54 dm <sup>3</sup>
4058075271555	Shipping carton box 8	760 mm x 300 mm x 225 mm	7960.00 g	51.30 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.