

PRODUCT FAMILY DATASHEET

LED OFFICE LINE GRID DIM

Dimmable luminaire for ceiling and pendant mounting with a grid for glare reduction

AREAS OF APPLICATION

- Indoor applications
- Home offices
- General indoor illumination
- Kitchens, workspaces



PRODUCT BENEFITS

- Energy savings thanks to dimming in three steps
- Flexible mounting options
- Functional and minimalistic design

PRODUCT FEATURES

- Replacement for traditional T8 luminaires
- For ceiling mounting or pendant mounting
- Material: Aluminium (Housing), Polycarbonate (Diffusor)
- Lifetime: up to 25,000 h
- Click-DIM version: dimmable in three steps by repeated switching
- GRID Version with included louver grid
- Lengths available: 0.6 m, 1.2 m
- Color temperature: 4,000 K





TECHNICAL DATA

Product description	Electrical data			Photometrical data		Light technical data	Dimensions & weight				Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Beam angle	Length	Width	Height	Product weight	Body material
LED Office Line Grid DIM 600 mm 25 W 4000 K	25.00 W	220...240 V	50/60 Hz	4000 K	2000 lm	105.00 °	595.0 mm	134.0 mm	46.0 mm	827.00 g	Aluminum
LED Office Line Grid DIM 1200 mm 50 W 4000 K	50.00 W	220...240 V	50/60 Hz	4000 K	4000 lm	105.00 °	1195 mm	134.0 mm	46.0 mm	1567.00 g	Aluminum

Product description	Housing color	Product color	Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
			Ambient temperature range	Number of switching cycles	Dimmable	Type of connection	Protection class	Type of protection
LED Office Line Grid DIM 600 mm 25 W 4000 K	White	White	-20...+40 °C	25000	Yes	Screw terminal	I	IP20
LED Office Line Grid DIM 1200 mm 50 W 4000 K	White	White	-20...+40 °C	25000	Yes	Screw terminal	I	IP20

Product description	Logistical data
	ErP For end-consumer
LED Office Line Grid DIM 600 mm 25 W 4000 K	yes
LED Office Line Grid DIM 1200 mm 50 W 4000 K	yes



LED Office Line Grid DIM 600 mm 25 W
4000 K

LED Office Line Grid DIM 1200 mm 50
W 4000 K

EQUIPMENT / ACCESSORIES

- Pendant mounting accessory included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075271555	Shipping carton box 8	760 mm x 300 mm x 225 mm	7960.00 g	51.30 dm ³
4058075271579	Shipping carton box 8	1360 mm x 300 mm x 225 mm	14433.00 g	91.80 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
--------------	------------------------------	--------------------------------------	--------------	--------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.