

PRODUCT FAMILY DATASHEET

SUBMARINE Integrated Slim Value

Flat and slim dampproof luminaires with integrated LED module

AREAS OF APPLICATION

- Basements, garages, warehouses



PRODUCT BENEFITS

- Easy installation, no tools required for connection
- Impressive for its low-profile design

PRODUCT FEATURES



- Damp-proof luminaires
- Dust-protected and jet-proof (IP65)
- Extremely low profile
- Not dimmable



TECHNICAL DATA

Product description	Electrical data			Photometrical data		Light technical data	Dimensions & weight				Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Beam angle	Length	Width	Height	Product weight	Body material
SubMARINE Integrated Slim Value 600 10 W 4000 K	10.00 W	220...240 V	50/60 Hz	4000 K	900 lm	120 °	715.0 mm	53.0 mm	35.0 mm	194.00 g	Polycarbonate (PC)
SubMARINE Integrated Slim Value 1200 18 W 4000 K	18.00 W	220...240 V	50/60 Hz	4000 K	1600 lm	120 °	1245 mm	53.0 mm	35.0 mm	299.00 g	Polycarbonate (PC)
SubMARINE Integrated Slim Value 1500 24 W 4000 K	24.00 W	220...240 V	50/60 Hz	4000 K	2160 lm	120 °	1525 mm	53.0 mm	35.0 mm	385.00 g	Polycarbonate (PC)

Product description	Housing color	Product color	Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
			Ambient temperature range	Number of switching cycles	Dimmable	Type of connection	Protection class	Type of protection
SubMARINE Integrated Slim Value 600 10 W 4000 K	White	White	-20...+35 °C	100000	No	Terminal, 2-Pole (L, N)	II	IP65
SubMARINE Integrated Slim Value 1200 18 W 4000 K	White	White	-20...+35 °C	100000	No	Terminal, 2-Pole (L, N)	II	IP65
SubMARINE Integrated Slim Value 1500 24 W 4000 K	White	White	-20...+35 °C	100000	No	Terminal, 2-Pole (L, N)	II	IP65



SubMARINE Integrated Slim Value 600
10 W 4000 K

SubMARINE Integrated Slim Value 1200
18 W 4000 K

SubMARINE Integrated Slim Value 1500
24 W 4000 K

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075266407	Shipping carton box 20	750 mm x 249 mm x 225 mm	4809.00 g	42.02 dm ³
4058075266421	Shipping carton box 20	1280 mm x 249 mm x 225 mm	7203.00 g	71.71 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075266445	Shipping carton box 20	1560 mm x 249 mm x 225 mm	9078.00 g	87.40 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.