

# PRODUCT FAMILY DATASHEET

## LED SPECIAL T SLIM

Slim LED lamps with B15d base



---

### AREAS OF APPLICATION

- Small designer luminaires
- Luxurious living areas
- Outdoor applications only in suitable luminaires

---

### PRODUCT BENEFITS

- Easy replacement of halogen lamps thanks to compact design
- Ideal in particular for many small designer luminaires
- Long lifetime of up to 15,000 h
- Very low energy consumption
- Lower thermal output (compared with the standard reference product)
- Three year guarantee

---

### PRODUCT FEATURES

- LED replacement for halogen lamps with B15d base
- Good quality of light; color rendering index  $R_a: \geq 80$ ; constant chromaticity
- Not dimmable




TECHNICAL DATA

Product description	Electrical data				Photometrical data				
	Nominal wattage	Nominal voltage	Max. lamp no. on circuit break. 10 A (B)	Max. lamp no. on circuit break. 16 A (B)	Nominal luminous flux	Rated luminous flux	Lumen main.fact.at end of nom.life time	Light color (designation)	Color temperature
SPC.T SLIM 60 320° 6.3 W/2700K B15d <sup>1)</sup>	6.30 W	220...240 V	15	25	806 lm	806 lm	0.70	Warm White	2700 K

Product description	Light technical data		Dimensions & weight		Temperatures & operating conditions		Lifespan		
	Luminous flux	Color rendering index Ra	Warm-up time (60 %)	Beam angle	Overall length	Diameter	Ambient temperature range	Nominal lamp life time	Number of switching cycles
SPC.T SLIM 60 320° 6.3 W/2700K B15d <sup>1)</sup>	806 lm	≥80	< 0.50 s	320 °	90.0 mm	18.0 mm	-20...+40 °C	15000 h	100000

Product description	Additional product data			Capabilities	Certificates & standards	
	Base (standard designation)	Mercury content	Mercury-free	Dimmable	Energy efficiency class	Energy consumption
SPC.T SLIM 60 320° 6.3 W/2700K B15d <sup>1)</sup>	B15d	0.0 mg	Yes	No	A++	7 kWh/1000h

<sup>1)</sup> All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value



SPC.T SLIM 60 320° 6.3 W/2700K B15d

#### SAFETY ADVICE

- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

#### APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075272033	Shipping carton box 4	96 mm x 90 mm x 109 mm	183.00 g	0.94 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### REFERENCES / LINKS

For further products and actual information concerning LED lamps see

- ▶ [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.