

PRODUCT FAMILY DATASHEET

LED SQUARE IP44

Luminaires with two selectable color temperatures via wall switch

AREAS OF APPLICATION

- Wall and ceiling surface mounting
- Bathrooms (IP44)
- Indoor applications



PRODUCT BENEFITS

- Homogenous illumination
- Easy and quick installation

PRODUCT FEATURES


- Color temperature selectable via wall switch (3000 K, 4000 K)
- Type of protection: IP44



TECHNICAL DATA

Product description	Electrical data			Photometrical data		Light technical data	Dimensions & weight				Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Beam angle	Length	Width	Height	Product weight	Body material
LED SQUARE IP44 CLICK CCT 14W 3000/4000 K	14.00 W	220...240 V	50/60 Hz	3000/4000 K	1250 lm	180 °	600.0 mm	40.0 mm	70.0 mm	800.00 g	Aluminum

Product description	Housing color	Product color	Cover material	Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
				Ambient temperature range	Number of switching cycles	Dimmable	Type of connection	Protection class	Type of protection
LED SQUARE IP44 CLICK CCT 14W 3000/4000 K	White	White	Polycarbonate (PC)	-20...+40 °C	15000	No	Terminal, 2-Pole (L, N)	II	IP44



LED SQUARE IP44 CLICK CCT 14W
3000/4000 K

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075399631	Shipping carton box 4	626 mm x 152 mm x 120 mm	2172.00 g	11.42 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.