

# PRODUCT FAMILY DATASHEET

## LED STRIP SUPERIOR-2000 PROTECTED

IP67 protected LED strips with 2000 lm/m for professional applications with very good color rendering and lifetime



---

### Areas of application

- General indoor illumination
- General outdoor illumination
- Industry
- Offices, retail outlets and conference rooms
- Architecture lighting

---

### Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy installation, no tools required for connection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Suitable for use in damp conditions thanks to high type of protection
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides

---

### Product features

- Flexible and cuttable LED strip
- Smallest cuttable unit: 50 mm
- Lifetime (L80/B10): up to 60,000 h at  $T_p: 45^\circ\text{C}$
- Luminous flux: 2000 lm/m
- Very good color rendering index  $R_a: > 90$
- Initial color consistency:  $\leq 3$  SDCM
- Large range of color temperatures: from warm white to cool daylight
- IESNA LM 79, LM80 compliant
- Type of protection: IP67
- Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)



- UV resistance (acc. IEC 60068-2-5)
- Salt mist resistance (acc. IEC 60068-2-52)



## TECHNICAL DATA

### Electrical data

Product description	Nominal wattage	Construction wattage	Nominal wattage per meter	Nominal voltage	Input voltage range
LS SUP -2000/940/3.5/IP67	72.00 W	72.00 W	20.6 W	24 V <sup>1)</sup>	23...25 V <sup>1)</sup>
LS SUP -2000/930/3.5/IP67	72.00 W	72.00 W	20.6 W	24 V <sup>1)</sup>	23...25 V <sup>1)</sup>
LS SUP -2000/960/3.5/IP67	72.00 W	72.00 W	20.6 W	24 V <sup>1)</sup>	23...25 V <sup>1)</sup>
LS SUP -2000/927/3.5/IP67	72.00 W	72.00 W	20.6 W	24 V <sup>1)</sup>	23...25 V <sup>1)</sup>

Product description	Reverse Voltage	Type of current	Nominal current
LS SUP -2000/940/3.5/IP67	25 V <sup>1)</sup>	DC	3570 mA
LS SUP -2000/930/3.5/IP67	25 V <sup>1)</sup>	DC	3570 mA
LS SUP -2000/960/3.5/IP67	25 V <sup>1)</sup>	DC	3570 mA
LS SUP -2000/927/3.5/IP67	25 V <sup>1)</sup>	DC	3570 mA

1) V<sub>DC</sub>

### Photometrical data

Product description	Luminous efficacy	Luminous flux	Luminous flux per meter	Luminous flux per module chain	Color temperature
LS SUP -2000/940/3.5/IP67	96 lm/W	7000 lm	2000 lm	7000 lm	4000 K
LS SUP -2000/930/3.5/IP67	89 lm/W	6475 lm	1850 lm	6475 lm	3000 K
LS SUP -2000/960/3.5/IP67	96 lm/W	7000 lm	2000 lm	7000 lm	6000 K
LS SUP -2000/927/3.5/IP67	89 lm/W	6475 lm	1850 lm	6475 lm	2700 K

Product description	Color rendering index Ra	Light color LED	Light color (designation)	Standard deviation of color matching
LS SUP -2000/940/3.5/IP67	> 90	Cool white	Cool White	≤3 sdc <sub>m</sub>
LS SUP -2000/930/3.5/IP67	> 90	White	White	≤3 sdc <sub>m</sub>
LS SUP -2000/960/3.5/IP67	> 90	Daylight	Cool Daylight	≤3 sdc <sub>m</sub>
LS SUP -2000/927/3.5/IP67	> 90	Warm white	Warm White	≤3 sdc <sub>m</sub>

### Light technical data

Product description	Beam angle
LS SUP -2000/940/3.5/IP67	120 °
LS SUP -2000/930/3.5/IP67	120 °
LS SUP -2000/960/3.5/IP67	120 °



Product description	Beam angle
LS SUP -2000/927/3.5/IP67	120 °

## LED MODULE INFORMATION

Product description	Number of LEDs per meter	Number of LEDs per module	Number of LEDs per smallest unit
LS SUP -2000/940/3.5/IP67	140	490	7
LS SUP -2000/930/3.5/IP67	140	490	7
LS SUP -2000/960/3.5/IP67	140	490	7
LS SUP -2000/927/3.5/IP67	140	490	7

## Dimensions & Weight

Product description	Length	Length – smallest unit	Cable length	Width
LS SUP -2000/940/3.5/IP67	3500.00 mm	50,0 mm	500.000	13.00 mm
LS SUP -2000/930/3.5/IP67	3500.00 mm	50,0 mm	500.000	13.00 mm
LS SUP -2000/960/3.5/IP67	3500.00 mm	50,0 mm	500.000	13.00 mm
LS SUP -2000/927/3.5/IP67	3500.00 mm	50,0 mm	500.000	13.00 mm

Product description	Width (incl. round luminaires)	Height	Height (incl. round luminaires)	Prewired	Conductor cross section
LS SUP -2000/940/3.5/IP67	13.00 mm	3.70 mm	3.70 mm	Yes	0.5 mm <sup>2</sup>
LS SUP -2000/930/3.5/IP67	13.00 mm	3.70 mm	3.70 mm	Yes	0.5 mm <sup>2</sup>
LS SUP -2000/960/3.5/IP67	13.00 mm	3.70 mm	3.70 mm	Yes	0.5 mm <sup>2</sup>
LS SUP -2000/927/3.5/IP67	13.00 mm	3.70 mm	3.70 mm	Yes	0.5 mm <sup>2</sup>

Product description	LED pitch	Short pitch	Product weight
LS SUP -2000/940/3.5/IP67	7.14 mm	Yes	190.00 g
LS SUP -2000/930/3.5/IP67	7.14 mm	Yes	190.00 g
LS SUP -2000/960/3.5/IP67	7.14 mm	Yes	190.00 g
LS SUP -2000/927/3.5/IP67	7.14 mm	Yes	190.00 g

## Colors & materials

Product description	Cover material
LS SUP -2000/940/3.5/IP67	Silicone
LS SUP -2000/930/3.5/IP67	Silicone
LS SUP -2000/960/3.5/IP67	Silicone



Product description	Cover material
LS SUP -2000/927/3.5/IP67	Silicone

### Temperatures & operating conditions

Product description	Ambient temperature range	Maximum temperature at tc test point	Temperature range in operation	Performance temp. acc. to IEC 62717
LS SUP -2000/940/3.5/IP67	-20...+50 °C <sup>1)</sup>	70 °C <sup>2)</sup>	-20...+70 °C <sup>3)</sup>	45 °C
LS SUP -2000/930/3.5/IP67	-20...+50 °C <sup>1)</sup>	70 °C <sup>2)</sup>	-20...+70 °C <sup>3)</sup>	45 °C
LS SUP -2000/960/3.5/IP67	-20...+50 °C <sup>1)</sup>	70 °C <sup>2)</sup>	-20...+70 °C <sup>3)</sup>	45 °C
LS SUP -2000/927/3.5/IP67	-20...+50 °C <sup>1)</sup>	70 °C <sup>2)</sup>	-20...+70 °C <sup>3)</sup>	45 °C

1) Providing that temperature at T<sub>c</sub> point is below max value during operation

2) Exceeding the maximum specified ratings can reduce expected life time or destroy the LED strip

3) At the T<sub>c</sub> point

### Lifespan

Product description	Nominal lamp life time
LS SUP -2000/940/3.5/IP67	60000 h
LS SUP -2000/930/3.5/IP67	60000 h
LS SUP -2000/960/3.5/IP67	60000 h
LS SUP -2000/927/3.5/IP67	60000 h

### Capabilities

Product description	Dimmable	Lowest bending radius	Self-adhesive	Reverse polarity protection
LS SUP -2000/940/3.5/IP67	Yes <sup>1)</sup>	50 mm	Yes	Up to maximum 25 V <sub>DC</sub>
LS SUP -2000/930/3.5/IP67	Yes <sup>1)</sup>	50 mm	Yes	Up to maximum 25 V <sub>DC</sub>
LS SUP -2000/960/3.5/IP67	Yes <sup>1)</sup>	50 mm	Yes	Up to maximum 25 V <sub>DC</sub>
LS SUP -2000/927/3.5/IP67	Yes <sup>1)</sup>	50 mm	Yes	Up to maximum 25 V <sub>DC</sub>

1) Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)

### Certificates & Standards

Product description	Approval marks – approval	Standards	Type of protection	Energy consumption	Energy efficiency class
LS SUP -2000/940/3.5/IP67	ENEC 25 / TUV / RoHS / CE / REACH	Acc. to IEC 62031 / Acc. to IEC 62493 / Acc. to IEC TR 62778 / Acc. to EN 50581 / Acc. to EN 62031	IP67	79.20 kWh/1000h	A+



Product description	Approval marks – approval	Standards	Type of protection	Energy consumption	Energy efficiency class
LS SUP -2000/930/3.5/IP67	ENEC 25 / TUV / RoHS / CE / REACH	Acc. to IEC 62031 / Acc. to IEC 62493 / Acc. to IEC TR 62778 / Acc. to EN 50581 / Acc. to EN 62031	IP67	79.20 kWh/1000h	A+
LS SUP -2000/960/3.5/IP67	ENEC 25 / TUV / RoHS / CE / REACH	Acc. to IEC 62031 / Acc. to IEC 62493 / Acc. to IEC TR 62778 / Acc. to EN 50581 / Acc. to EN 62031	IP67	79.20 kWh/1000h	A+
LS SUP -2000/927/3.5/IP67	ENEC 25 / TUV / RoHS / CE / REACH	Acc. to IEC 62031 / Acc. to IEC 62493 / Acc. to IEC TR 62778 / Acc. to EN 50581 / Acc. to EN 62031	IP67	79.20 kWh/1000h	A+

Product description	Salt mist resistance acc. IEC 60068-2-52	UV resistance acc. IEC 60068-2-5
LS SUP -2000/940/3.5/IP67	Yes	Yes
LS SUP -2000/930/3.5/IP67	Yes	Yes
LS SUP -2000/960/3.5/IP67	Yes	Yes
LS SUP -2000/927/3.5/IP67	Yes	Yes

**LOGISTICAL DATA**

Product description	Temperature range at storage
LS SUP -2000/940/3.5/IP67	-35...+85 °C
LS SUP -2000/930/3.5/IP67	-35...+85 °C
LS SUP -2000/960/3.5/IP67	-35...+85 °C
LS SUP -2000/927/3.5/IP67	-35...+85 °C

**Energy labelling regulation data acc EU 2019/2015**

Product description	Correlated colour temperature type
LS SUP -2000/940/3.5/IP67	SINGLE_VALUE
LS SUP -2000/930/3.5/IP67	SINGLE_VALUE
LS SUP -2000/960/3.5/IP67	SINGLE_VALUE
LS SUP -2000/927/3.5/IP67	SINGLE_VALUE

**EQUIPMENT / ACCESSORIES**

- Connectors, profiles and covers for several mounting options available
- Endcaps have to be ordered separately

**APPLICATION ADVICE**

For more detailed application information and graphics please see product datasheet.



---

## ADDITIONAL PRODUCT INFORMATION

- All the technical parameters apply to the entire LED module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values.
- All LED strips have a self-adhesive tape on the reverse side. LED strips can be attached to suitable materials, e.g. aluminum profiles. The surface of the material must be free of grease, oil, silicone and dirt particles. The adhesive tape can be used only one time, if the LED strip will be removed from the mounting surface, there could be a damage of the LED strips and the mounting material. The surface temperature of the mounting material should be in the temperature range of 18°C...35°C. Complete adhesion takes up to 72 h.
- According IPC 6013C – Use A the LED strips are designed for static installation. Vibrations, respective torsion and elongation/compression must be considered.
- In a wide temperature range operation field (e.g. outdoor installation) and a LED strip length with more than 2m suitable mounting surface is required. To avoid stress due to mismatch in expansion of the different materials, there should be an extra thicker adhesive tape between LED strip and mounting surface. Additionally, the LED strip should have enough space for thermal expansion at higher temperatures.
- Compensation due to chemical corrosion is excluded. A suitable protection against corrosive agents such as moisture, condensation etc. must be provided. Hydrogen sulfide (H<sub>2</sub>S) will cause an accelerated corrosion which leads to shortened lifetime or premature failure.
- IP00 LED strips have not surface coating. Consequently, they have no protection against contact and corrosion.
- Installation of the LED strip has to be done by a qualified electrician.
- Handle with care to avoid mechanical product damage
- If the maximum operating and storage temperature ratings will be exceeded, the expected lifetime will be reduced or even the LED strip will be destroyed. It is not allowed to operate the LED strip over the specified T<sub>c</sub> temperature (acc. EN 60598-1 under steady state conditions)
- It is not allowed to exceed the maximum operation voltage. This could cause a hazardous overload and will destroy the LED strip.
- The applicable electrical and safety standards have to be maintained for a LED strip installations
- Pay attention on correct polarity. Incorrect polarity or wrong wiring can cause unpredictable permanent damage or even failure of the product.
- Galvanic Insulation between LED strip and mounting surface must be ensured. This Insulation is needed especially in the area of connections or cut ends.
- In installations of LED strips ESD safety must be taken in account. Adequate precautions during installation and operation for the products are required.
- LED strip can be operated only by a SELV LED driver, which comply with the applicable lighting standards and fits to LED strips rating. A safety operation of the LED strips require a SELV LED driver with an electronically stabilized power supply protection against short circuits, overload and overheating.
- To avoid a damage of the LED strip, the unmounted LED strip should be handled and stored only in the original LEDVANCE packaging (wheel / ESD bag). Repacking is not allowed. Cutted IP 6x LED strips can be stored only with mounted endcaps.

---

## SALES AND TECHNICAL SUPPORT

Sales and Technical Support [www.ledvance.com](http://www.ledvance.com)

---

## COUNTRY SPECIFIC INFORMATION

Product description	Product code	METEL-Code	SEG number	STK number	UK Org
LS SUP -2000/940/3.5/IP67	4058075237162	-	7507114	4246036	-
LS SUP -2000/930/3.5/IP67	4058075237148	-	7507113	4246035	-
LS SUP -2000/960/3.5/IP67	4058075237209	-	-	4246037	-
LS SUP -2000/927/3.5/IP67	4058075237124	-	7507112	4246034	-

---

## DOWNLOAD DATA



## DOWNLOAD DATA



User instruction  
LED STRIP SUPERIOR IP67



Declarations of conformity  
EU Declaration of Conformity 3956203 LS SUP



LDT file (Eulumdat)  
LS SUP-2000-940-3.5-IP67



Catalogs  
LEDVANCE LED Strip System - Wave 2 - Fall 2020 (EN)



User instruction  
LED STRIP SUPERIOR IP67



Declarations of conformity  
EU Declaration of Conformity 3956203 LS SUP



LDT file (Eulumdat)  
LS SUP-2000-930-3.5-IP67



Catalogs  
LEDVANCE LED Strip System - Wave 2 - Fall 2020 (EN)



User instruction  
LED STRIP SUPERIOR IP67



Certificates  
EAEC N RU D-DE.MYu62.B.01038 20 13.03.2020-12.03.2025



Declarations of conformity  
EU Declaration of Conformity 3956203 LS SUP



LDT file (Eulumdat)  
LS SUP-2000-960-3.5-IP67



Catalogs  
LEDVANCE LED Strip System - Wave 2 - Fall 2020 (EN)



User instruction  
LED STRIP SUPERIOR IP67



Certificates  
EAEC N RU D-DE.MYu62.B.01038 20 13.03.2020-12.03.2025



Declarations of conformity  
EU Declaration of Conformity 3956203 LS SUP



LDT file (Eulumdat)  
LS SUP-2000-927-3.5-IP67



Catalogs  
LEDVANCE LED Strip System - Wave 2 - Fall 2020 (EN)





## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075237162	Folding box 1	336 mm x 30 mm x 334 mm	271.00 g	3.37 dm <sup>3</sup>
4058075237148	Folding box 1	336 mm x 30 mm x 334 mm	271.00 g	3.37 dm <sup>3</sup>
4058075237209	Folding box 1	336 mm x 30 mm x 334 mm	271.00 g	3.37 dm <sup>3</sup>
4058075237124	Folding box 1	336 mm x 30 mm x 334 mm	271.00 g	3.37 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## ACCESSORIES MANDATORY

Product description	Accessory name	Accessory code
LS SUP -2000/940/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240032
LS SUP -2000/940/3.5/IP67	LED DRIVER VALUE -150/220-240/24	▶ 4058075240179
LS SUP -2000/940/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075240117
LS SUP -2000/940/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240155
LS SUP -2000/940/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075239975
LS SUP -2000/940/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075239937
LS SUP -2000/940/3.5/IP67	LED DRIVER VALUE -120/220-240/24	▶ 4058075240131
LS SUP -2000/940/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075240070
LS SUP -2000/930/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075239975
LS SUP -2000/930/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240032
LS SUP -2000/930/3.5/IP67	LED DRIVER VALUE -120/220-240/24	▶ 4058075240131
LS SUP -2000/930/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075240117
LS SUP -2000/930/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075240070
LS SUP -2000/930/3.5/IP67	LED DRIVER VALUE -150/220-240/24	▶ 4058075240179
LS SUP -2000/930/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075239937
LS SUP -2000/930/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240155
LS SUP -2000/960/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075240070
LS SUP -2000/960/3.5/IP67	LED DRIVER VALUE -150/220-240/24	▶ 4058075240179
LS SUP -2000/960/3.5/IP67	LED DRIVER VALUE -120/220-240/24	▶ 4058075240131
LS SUP -2000/960/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240032
LS SUP -2000/960/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075239937



Product description	Accessory name	Accessory code
LS SUP -2000/960/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240155
LS SUP -2000/960/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075239975
LS SUP -2000/960/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075240117
LS SUP -2000/927/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075240070
LS SUP -2000/927/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240032
LS SUP -2000/927/3.5/IP67	LED DRIVER VALUE -150/220-240/24	▶ 4058075240179
LS SUP -2000/927/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -100/220-240/24/P	▶ 4058075239937
LS SUP -2000/927/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -250/220-240/24/P	▶ 4058075240155
LS SUP -2000/927/3.5/IP67	LED DRIVER OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075239975
LS SUP -2000/927/3.5/IP67	LED DRIVER VALUE -120/220-240/24	▶ 4058075240131
LS SUP -2000/927/3.5/IP67	LED DRIVER 1-10 V DIM OUTDOOR PERFORMANCE -150/220-240/24/P	▶ 4058075240117

## ACCESSORIES OPTIONAL

Product description	Accessory name	Accessory code
LS SUP -2000/940/3.5/IP67	Profiles for LED Strips Superior Class -PF01/U/16X10/13/1	▶ 4058075304741
LS SUP -2000/940/3.5/IP67	Wide Profiles for LED Strips -PW03/U/26X26/14/2	▶ 4058075401501
LS SUP -2000/940/3.5/IP67	Profiles for LED Strips Superior Class -PFS01/16X10/13/0,015	▶ 4058075304710
LS SUP -2000/940/3.5/IP67	Connectors for LED Strips Superior Class -SEF	▶ 4058075304680
LS SUP -2000/940/3.5/IP67	Wide Profiles for LED Strips -PW02/UW/39X26/14/1	▶ 4058075278134
LS SUP -2000/940/3.5/IP67	Connectors for LED Strips Superior Class -SE/P + SILICONE SEAL	▶ 4058075304659
LS SUP -2000/940/3.5/IP67	Wide Profiles for LED Strips -PW01/U/26X8/14/2	▶ 4058075401440
LS SUP -2000/940/3.5/IP67	Wide Profiles for LED Strips -PW03/U/26X26/14/1	▶ 4058075278165
LS SUP -2000/940/3.5/IP67	Wide Profiles for LED Strips -PW01/U/26X8/14/1	▶ 4058075278103
LS SUP -2000/940/3.5/IP67	Wide Profiles for LED Strips -PW02/UW/39X26/14/2	▶ 4058075401471
LS SUP -2000/930/3.5/IP67	Connectors for LED Strips Superior Class -SEF	▶ 4058075304680
LS SUP -2000/930/3.5/IP67	Wide Profiles for LED Strips -PW03/U/26X26/14/1	▶ 4058075278165
LS SUP -2000/930/3.5/IP67	Wide Profiles for LED Strips -PW02/UW/39X26/14/2	▶ 4058075401471
LS SUP -2000/930/3.5/IP67	Wide Profiles for LED Strips -PW02/UW/39X26/14/1	▶ 4058075278134
LS SUP -2000/930/3.5/IP67	Wide Profiles for LED Strips -PW01/U/26X8/14/1	▶ 4058075278103
LS SUP -2000/930/3.5/IP67	Wide Profiles for LED Strips -PW01/U/26X8/14/2	▶ 4058075401440
LS SUP -2000/930/3.5/IP67	Wide Profiles for LED Strips -PW03/U/26X26/14/2	▶ 4058075401501
LS SUP -2000/930/3.5/IP67	Connectors for LED Strips Superior Class -SE/P + SILICONE SEAL	▶ 4058075304659
LS SUP -2000/930/3.5/IP67	Profiles for LED Strips Superior Class -PFS01/16X10/13/0,015	▶ 4058075304710
LS SUP -2000/930/3.5/IP67	Profiles for LED Strips Superior Class -PF01/U/16X10/13/1	▶ 4058075304741



Product description	Accessory name	Accessory code
LS SUP -2000/960/3.5/IP67	Connectors for LED Strips Superior Class -SE/P + SILICONE SEAL	▶ 4058075304659
LS SUP -2000/960/3.5/IP67	Wide Profiles for LED Strips -PW03/U/26X26/14/1	▶ 4058075278165
LS SUP -2000/960/3.5/IP67	Wide Profiles for LED Strips -PW02/UW/39X26/14/2	▶ 4058075401471
LS SUP -2000/960/3.5/IP67	Wide Profiles for LED Strips -PW01/U/26X8/14/1	▶ 4058075278103
LS SUP -2000/960/3.5/IP67	Wide Profiles for LED Strips -PW03/U/26X26/14/2	▶ 4058075401501
LS SUP -2000/960/3.5/IP67	Connectors for LED Strips Superior Class -SEF	▶ 4058075304680
LS SUP -2000/960/3.5/IP67	Profiles for LED Strips Superior Class -PFS01/16X10/13/0,015	▶ 4058075304710
LS SUP -2000/960/3.5/IP67	Wide Profiles for LED Strips -PW02/UW/39X26/14/1	▶ 4058075278134
LS SUP -2000/960/3.5/IP67	Wide Profiles for LED Strips -PW01/U/26X8/14/2	▶ 4058075401440
LS SUP -2000/960/3.5/IP67	Profiles for LED Strips Superior Class -PF01/U/16X10/13/1	▶ 4058075304741
LS SUP -2000/927/3.5/IP67	Wide Profiles for LED Strips -PW03/U/26X26/14/2	▶ 4058075401501
LS SUP -2000/927/3.5/IP67	Connectors for LED Strips Superior Class -SEF	▶ 4058075304680
LS SUP -2000/927/3.5/IP67	Wide Profiles for LED Strips -PW02/UW/39X26/14/2	▶ 4058075401471
LS SUP -2000/927/3.5/IP67	Wide Profiles for LED Strips -PW02/UW/39X26/14/1	▶ 4058075278134
LS SUP -2000/927/3.5/IP67	Wide Profiles for LED Strips -PW01/U/26X8/14/2	▶ 4058075401440
LS SUP -2000/927/3.5/IP67	Profiles for LED Strips Superior Class -PF01/U/16X10/13/1	▶ 4058075304741
LS SUP -2000/927/3.5/IP67	Wide Profiles for LED Strips -PW01/U/26X8/14/1	▶ 4058075278103
LS SUP -2000/927/3.5/IP67	Connectors for LED Strips Superior Class -SE/P + SILICONE SEAL	▶ 4058075304659
LS SUP -2000/927/3.5/IP67	Profiles for LED Strips Superior Class -PFS01/16X10/13/0,015	▶ 4058075304710
LS SUP -2000/927/3.5/IP67	Wide Profiles for LED Strips -PW03/U/26X26/14/1	▶ 4058075278165

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

