

# PRODUCT DATASHEET SUN@HOME Orbis Cross

Sun@Home Wall luminaires | Wall Lights with Human Centric Lighting Technology



## Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

#### **Product benefits**

- Enable increased concentration and efficiency
- Improve overall activity level and daytime alertness
- Improve sleeping rhythm and -intensity
- Improve optic convenience
- Enables an improved level of clean-air-safety by killing residential germs and bad odors
- Homogenous light distribution
- Easy and quick installation

#### **Product features**

- Adjustable color temperature via Tunable White: 2,200...5,000 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Innovative Fullspectrum SunLike LEDs with CRI95
- SunLike LEDs with reduced Blue Light in LED Spectrum



- Innovative luminaire coating-technology fighting household germs and odors
- Automated biorhythm feature

# TECHNICAL DATA

## Electrical data

Nominal wattage	12.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	52.000 mA
Inrush current	2.1 A
Power factor $\lambda$	> 0.70
Protection class	П
Operating mode	Mains voltage

# Photometrical data

Luminous flux	600 lm	
Total luminous flux of contained light sources	800 lm	
Luminous efficacy	60 lm/W	
Color temperature	22005000 K	
Reference control setting of contained light source (Kelvin)	2700 K	
Light color (designation)	Tunable White	
Color rendering index Ra	> 95	
Standard deviation of color matching	≤6 sdcm	
Flickering metric (Pst LM)	≤ 1 %	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	110 °	

# Dimensions & Weight

Length	309.00 mm
Width	200.00 mm
Height	106.00 mm
Product weight	770.00 g

HCL SMART Wall UpDown TW

# Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection	Terminal	
Type of protection	IP20	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Wall	
Application environment	Indoor	
With light source	Yes	

## Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	10000

# **Emergency lighting**

Integrated test switch	No
------------------------	----

#### Certificates & Standards

Standards	CE / UKCA	
Luminaire with limited surface temperature, "D sign"	No	
Replaceable light source (EPREL)	Not replaceable	

## **EQUIPMENT / ACCESSORIES**

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Complete mounting and connecting accessories included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

#### DOWNLOAD DATA

	Documents and certificates	Document name			
POF	User instruction / safety instructions	SUN@HOME ORBIS CROSS			
POF	Legal information	SUN@HOME			
POF	Declarations of conformity	SUN HOME ORBIS CROSS TW			
POF	Declarations of conformity UKCA	SUNATHOME			
	CAD/BIM files	Document name			
	BIM Step 3D	Sun@Home orbis			

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075575936	Folding box 1	82 mm x 132 mm x 354 mm	873.00 g	3.83 dm <sup>3</sup>
4058075575943	Shipping box 8	349 mm x 285 mm x 380 mm	7429.00 g	37.80 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.