

# PRODUCT DATASHEET LS AY -CSW/P2/50/P

Connectors for LED Strips PFM and VAL | Connector for LED Strips



# Areas of application

- General indoor illumination

#### **Product benefits**

- Easy installation of connector, no manual wiring required
- Tool-free installation

# **TECHNICAL DATA**

### Electrical data

Nominal voltage	24 V
Nominal current	5000 mA

# Dimensions & Weight

Length	102.4 mm
Cable length	50 mm
Width	15.0 mm
Height	7.0 mm
Cable cross-section, input side	0.5 mm <sup>2</sup>
Product weight	7.00 g

#### Colors & materials

Product color	Transparent
---------------	-------------

# Temperatures & operating conditions

Ambient temperature range	-20+55 °C
---------------------------	-----------

# Certificates & Standards

Type of protection IP67	
-------------------------	--

#### LOGISTICAL DATA

Temperature range at storage	-20+80 °C
------------------------------	-----------

# DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	LS AY

Tender texts	Document name
Tender documents	Connectors for LED Strips PFM and VAL CSWP250P-EN

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075727496	BAG 2	80 mm x 120 mm x 5 mm	15.00 g	0.05 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075727502	Shipping box 100	180 mm x 100 mm x 180 mm	829.00 g	3.24 dm <sup>3</sup>
4058075727519	Shipping box 1,000	520 mm x 380 mm x 210 mm	9058.00 g	41.50 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.