

PRODUCT DATASHEET SMART+ Wifi Planon 1200x100mm TW

SMART+ Planon Frameless TW | Frameless panel luminaires with WiFi technology

Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



Product benefits

- Easy and quick installation

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Dimmable
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Network protocol: WiFi



TECHNICAL DATA

Electrical data

| Nominal wattage35.00 WNominal voltage220240 VMains frequency5060 HzNominal current176.000 mAMax. number of luminaires per miniature circuit breaker B1616Max. number of luminaires per miniature circuit breaker C1624Power factor λ> 0.90Total harmonic distortion< 20 %Protection classIIOperating modeMains voltage | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------|
| Mains frequency5060 HzNominal current176.000 mAMax. number of luminaires per miniature circuit breaker B1616Max. number of luminaires per miniature circuit breaker C1624Power factor λ> 0.90Total harmonic distortion< 20 % | Nominal wattage | 35.00 W |
| Nominal current176.000 mAMax. number of luminaires per miniature circuit breaker B1616Max. number of luminaires per miniature circuit breaker C1624Power factor λ> 0.90Total harmonic distortion< 20 % | Nominal voltage | 220240 V |
| Max. number of luminaires per miniature circuit breaker B16 16 Max. number of luminaires per miniature circuit breaker C16 24 Power factor λ > 0.90 Total harmonic distortion < 20 % | Mains frequency | 5060 Hz |
| Max. number of luminaires per miniature circuit breaker C16 24 Power factor λ > 0.90 Total harmonic distortion < 20 % | Nominal current | 176.000 mA |
| Power factor λ > 0.90 Total harmonic distortion < 20 % Protection class II | Max. number of luminaires per miniature circuit breaker B16 | 16 |
| Total harmonic distortion < 20 % Protection class II | Max. number of luminaires per miniature circuit breaker C16 | 24 |
| Protection class II | Power factor λ | > 0.90 |
| | Total harmonic distortion | < 20 % |
| Operating mode Mains voltage | Protection class | II |
| | Operating mode | Mains voltage |

Photometrical data

| Luminous flux | 2500 lm | |
|------------------------------------------------|---------------|--|
| Total luminous flux of contained light sources | 4000 lm | |
| Luminous efficacy | 71 lm/W | |
| Color temperature | 30006500 K | |
| Light color (designation) | Tunable White | |
| Color rendering index Ra | > 80 | |
| Standard deviation of color matching | < 6 sdcm | |
| Flickering metric (Pst LM) | ≤1 | |
| Stroboscope effect metric (SVM) | ≤0.4 | |
| Photobiological safety group acc. to EN62778 | RG0 | |
| Photobiological safety group acc. to EN62471 | RG0 | |
| Beam angle | 110 ° | |

Dimensions & Weight

| Length | 1200.00 mm |
|----------------|------------|
| Width | 100.00 mm |
| Height | 63.00 mm |
| Product weight | 2260.00 g |

SMART WIFI PLANON FRAMELESS120X10

Materials & Colors

| Product color | White |
|--------------------------------------------|-------------------------------|
| Housing color | White |
| Body material | Aluminum |
| Cover material | Polymethylmethacrylate (PMMA) |
| Light emitting surface material | PMMA |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|---------------------------|-------------------------|
| Type of connection | Terminal, 2-Pole (L, N) |
| Type of protection | IP20 |
| Dimmable | Yes |
| Type of dimming | WiFi |
| Mounting type | Surface |
| Mounting location | Ceiling |
| Application environment | Indoor |
| With light source | No |

Lifespan

| Lifespan L70/B50 at 25 °C | 25000 h |
|----------------------------|---------|
| Number of switching cycles | 15000 |

Certificates & Standards

| Standards | CE / EAC / UKCA |
|------------------------------------------------------|-----------------|
| Luminaire with limited surface temperature, "D sign" | No |

Additional product data

| Pı | roduct remark | Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times. |
|----|---------------|----------------------------------------------------------------------------------------------------------------------------------|
| | | |

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| | Documents and certificates Document name | | |
|-----------------------------------------------------------------|------------------------------------------|-------------------------------------|--|
| User instruction / safety instructions SMART+ PLANON FRAMELESS | | SMART+ PLANON FRAMELESS | |
| PDF | Declarations of conformity | SMART WIFI PLANON FRAMELESS120X10TW | |
| PDF | Declarations of conformity UKCA | SMART WIFI AND SUNATHOME | |
| PDF | EU Data Act | SMART WiFi Lamps and Luminaires | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075484535 | Folding box 1 | 95 mm x 1,237 mm x 135 mm | 2758.00 g | 15.86 dm ³ |
| 4058075484542 | Shipping box 6 | 1,254 mm x 304 mm x 305 mm | 18044.00 g | 116.27 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.