

# PRODUCT DATASHEET SMART+ WIFI CONTACT SENSOR

SMART+ CONTACT SENSOR | SMART+ sensor to detect open doors and windows with WiFi technology



## Areas of application

- For indoor use only

## **Product benefits**

- Notification of contact status change
- Monitors the history of contact status
- Easy control of compatible SMART+ WiFi products based on contact status

# **Product features**

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Wireless smart contact sensor for status of windows and doors (open/close)
- Easy and flexible installation thanks to adhesive pad and wireless operation
- Rechargeable battery-powered (6 months lifetime per charging, 5 detections per day)
- Check the battery level by LEDVANCE SMART+ WiFi APP
- Network protocol: WiFi



## TECHNICAL DATA

# Electrical data

| Nominal voltage | 3,7 V   |
|-----------------|---------|
| Mains frequency | 0 Hz    |
| Operating mode  | Battery |

# **Dimensions & Weight**

| Product weight | 47.00 g  |
|----------------|----------|
| Length         | 72.00 mm |
| Width          | 31.00 mm |
| Height         | 24.00 mm |

#### Colors & materials

| Product color | White   |
|---------------|---------|
| Body material | Plastic |

#### Temperatures & operating conditions

| Ambient temperature range | -10+50 °C |
|---------------------------|-----------|
| 1 0                       |           |

# Capabilities

| Dimmable                         | No                              |
|----------------------------------|---------------------------------|
| Compatible smart home technology | Amazon Alexa / Google Assistant |

# **Certificates & Standards**

| Standards          | CE   |
|--------------------|------|
| Type of protection | IP20 |

# Safety advice

- Battery Warning: Keep out of reach for children. Swallowing can lead to chemical burns, perforation of soft tissue, and death. Severe burns can occur within 2 hours of ingestion. Seek medical attention immediately.

- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in

the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.

## DOWNLOAD DATA

|     | Documents and certificates  | Document name             |
|-----|-----------------------------|---------------------------|
| POF | Extended installation guide | CONTACT SENSOR            |
| POF | Declarations of conformity  | SMART WIFI CONTACT SENSOR |

# LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075730052 | Folding box<br>1             | 62 mm x 80 mm x 98 mm                | 86.00 g      | 0.49 dm <sup>3</sup>  |
| 4058075730069 | Shipping box<br>4            | 173 mm x 108 mm x 141 mm             | 417.00 g     | 2.63 dm <sup>3</sup>  |
| 4058075730076 | Shipping box<br>32           | 359 mm x 229 mm x 303 mm             | 3667.00 g    | 24.91 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.