

# PRODUCT DATASHEET SP RING D180 WT

SPOT RING | Refurbishment rings to reduce existing cut-out in recessed ceilings



- Refurbishment of existing cut-outs in recessed ceilings



### Product benefits

- Retrofit: Replacement of old recessed lights with LEDVANCE SPOTs FIX or ADJ in latest LED-technology
- Standardize: Reduce existing cut-outs to a standard cut-out of 68 mm
- Versatile: Refurbishment rings for padding cut-out holes from Ø68 Ø90 or Ø68 Ø115 or Ø115 Ø160 mm

# Product features

- Material: deep-drawn steel
- Suitable only for LEDVANCE SPOTs in 68 mm cut-out
- Silicon-pad protected springs



## TECHNICAL DATA

# Dimensions & Weight

Diameter	180 mm
Height	3 mm
Product weight	176.00 g



#### Materials & Colors

Product color	White
Body material	Steel

# Application & Mounting

Ambient temperature range	-20+40 °C
Mounting type	Recessed
Mounting location	Ceiling
Mounting diameter	115160 mm
Replaceable light source	No

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	UI SP FIX P and SP FIX ADJ
PDF	User instruction / safety instructions	UI SP DK FIX P
PDF	User instruction / safety instructions	UI SP AIR FIX P
PDF	Declarations of conformity	CE Declaration of Conformity SPOTLIGHT ACCESSORY

Tender texts	Document name
Tender documents	SPOT RING D180 WT-EN

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854013416	BAG 1	182 mm x 182 mm x 3 mm	180.00 g	0.10 dm <sup>3</sup>
4099854013423	Shipping box 20	365 mm x 185 mm x 240 mm	3935.00 g	16.21 dm <sup>3</sup>
4099854013430	Shipping box 60	580 mm x 385 mm x 270 mm	2345.00 g	60.29 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.