

PRODUCT DATASHEET TRUSYS FLEX P RAIL 1500 8P WT

TruSys® FLEX ENERGY RAIL 8-POLE | 8-pole mounting rail



Areas of application

- Industry halls, high rack warehouse, hardware stores



Product benefits

- Simple installation
- High flexibility thanks to three available lengths (1500 mm, 3000 mm, 4500 mm and 1500 mm end rail)
- Version of 600 mm rail to be used with TRUSYS FLEX SENSOR TRACK

Product features

- Through wired with 8 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	1650 mm
Width	70.2 mm
Height	38.8 mm
Product weight	1750.00 g



TRUSYS FLEX RAIL

Materials & Colors

Product color	White
Body material	Steel

Application & Mounting

	Mounting location	Ceiling
Ī	With light source	No
Replaceable light source		No

Certificates & Standards

|--|

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	TRUSYS FLEX P RAIL

	Documents and certificates	Document name
POF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Declarations of conformity	CE Declaration of Conformity TRUSYS FLEX
PDF	Declarations of conformity UKCA	UKCA Declaration of Conformity TRUSYS FLEX
	CAD/BIM files	Document name
RFA	BIM Revit 3D	TRUSYS FLEX

Tender texts	Document name
Tender documents	TruSys FLEX ENERGY RAIL 8-POLE 1500 8P WT-EN

TruSys FLEX ER 1500

LOGISTICAL DATA

CAD STEP 3D

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075781696	Sleeve 1	43 mm x 52 mm x 1,680 mm	1762.00 g	3.76 dm ³
4058075781702	Shipping box	1,720 mm x 191 mm x 141 mm	8118.00 g	46.16 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.