

# PRODUCT DATASHEET Tracklight Round Base White

Tracklight rail and base | Tracklight rail and base



## Areas of application

- Kitchens, living rooms, children's rooms or home offices
- Entrance areas

## Product benefits

- Timeless elegant design
- Made of solid aluminum with high-quality appearance

#### **Product features**

- Customisable modular tracklight system




## **TECHNICAL DATA**

## Electrical data

| Nominal voltage  | 220240 V |
|------------------|----------|
| Mains frequency  | 50/60 Hz |
| Protection class | 1        |

# Dimensions & Weight

| Diameter       | 100 mm  |
|----------------|---------|
| Height         | 32.0 mm |
| Product weight | 90.00 g |



TRACKLIGHT ROUND BASE BK

## Materials & Colors

| Product color | White              |
|---------------|--------------------|
| Body material | Polycarbonate (PC) |

# **Application & Mounting**

| Ambient temperature range | -20+40 °C       |
|---------------------------|-----------------|
| Type of connection        | Terminal, 2-pin |
| Type of protection        | IP20            |
| Mounting type             | Surface         |
| Mounting location         | All surfaces    |
| Replaceable light source  | No              |

# Certificates & Standards

| Standards      | CE / UKCA |
|----------------|-----------|
| Ball shot safe | No        |

## **Accessories Optional**

| Product image                                  | Product name                               | EAN           |  |
|--|--|---------------|--|
| \$0-3000 +\$                                   | Tracklight Flexible Connector White        | 4058075764088 |  |
|  | Tracklight Linear Connector White 40580757 |               |  |
| Tracklight Supply Connector White 405807       |  | 4058075763968 |  |
| Tracklight Cross Connector White               |  | 4058075764125 |  |
| Tracklight Corner Connector White 405807576404 |  | 4058075764040 |  |
| Tracklight Suspension Kit White                |  | 4058075764163 |  |

# Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

# DOWNLOAD DATA

|     | Documents and certificates Document name |                       |
|-----|--|-----------------------|
| PDF | User instruction / safety instructions   | TRACKLIGHT ROUND BASE |
| PDF | Declarations of conformity               | TRACKLIGHT            |

| Documents and certificates |                                 | Document name          |  |
|----------------------------|---------------------------------|------------------------|--|
| PDF                        | Declarations of conformity UKCA | TRACKLIGHT ACCESSORIES |  |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075764224 | BAG<br>1                     | 35 mm x 170 mm x 240 mm              | 98.00 g      | 1.43 dm <sup>3</sup> |
| 4099854114113 | Shipping box<br>8            | 290 mm x 130 mm x 110 mm             | 929.00 g     | 4.15 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.