

PRODUCT DATASHEET SMART+ Wifi Planon Frameless Sparkle 1200x300mm TW

SMART+ Planon Frameless Sparkle | Panel frameless Sparkle effect luminaires with WiFi technology



Areas of application

- Kitchens, living rooms, children's rooms or home offices
- Entrance areas

Product benefits

- Creating individual light scenes according to your needs with cold white to warm white (3000 K to 6500 K)
- Elegant design
- Frameless panel luminaire
- Sparkle effect that creates a sky night effect
- Easy and quick installation

Product features

- Ceiling luminaire with advanced LED technology
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Sparkle effect

1200x300mm TW



TECHNICAL DATA

Electrical data

Nominal wattage	38.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	164.000 mA
Inrush current time T _{h50}	1900 μs
Max. number of luminaires per miniature circuit breaker B16	10
Max. number of luminaires per miniature circuit breaker C16	18
Power factor λ	≥0.90
Total harmonic distortion	< 20 %
Protection class	I

Photometrical data

Luminous flux	2300 lm
Total luminous flux of contained light sources	4200 lm
Luminous efficacy	60 lm/W
Color temperature	30006500 K
Reference control setting of contained light source (Kelvin)	3000 K ¹⁾
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG1

¹⁾ Performing a reset will restore the default values set by the manufacturer

Dimensions & Weight

Length	1200.00 mm
Width	300.00 mm
Height	63.00 mm
Product weight	3200.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Application environment	Indoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.	
Number of illuminants	empty	

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	UI_SMART WIFI PLANONFL SPARK	
PDF	Extended installation guide	SMART+ WIFI INSTALLATION GUIDE	
PDF	Declarations of conformity	SMART WIFI	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075759589	Folding box 1	82 mm x 1,232 mm x 343 mm	4178.00 g	34.65 dm ³
4058075759596	Shipping box 2	1,253 mm x 183 mm x 368 mm	9397.00 g	84.38 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

1200x300mm TW