

# PRODUCT DATASHEET

## SMART+ WiFi Filament Globe 40 Multicolour E27

SMART+WIFI Filament Globe RGBTW | Classic Globe shape with filament design with WiFi technology



### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor applications only in suitable luminaires

### Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury
- Lower energy consumption than incandescent or halogen lamps

### Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi
- Lifetime up to 15,000 h
- Voice control works with Hey Google or Alexa




TECHNICAL DATA

Electrical data

Nominal wattage	4.8 W
Construction wattage	4.80 W
Nominal voltage	220...240 V
Nominal current	50 mA
Mains frequency	50/60 Hz
Power factor $\lambda$	0.40
Claimed equiv. conventional lamp power	40 W
Operating mode	AC Mains

Photometrical data

Light color (designation)	RGBTW
Lumen main.fact.at end of nom.life time	0.93
Standard deviation of color matching	$\leq 6$ sdcm
Nominal luminous flux	470 lm
Luminous flux	470 lm
Luminous efficacy	97 lm/W
Adjustable color temperature	2700...6500 K
Color temperature	2700...6500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	<1.0
Stroboscope effect metric (SVM)	<0.4



EPREL Data Spectral Diagram LEDr  
AC42286 AC42287 AC42288  
RGBTW

## Light technical data

Beam angle	320 °
Starting time	0.5 s

## Dimensions &amp; Weight



Product weight	100.00 g
Diameter	124.00 mm
Maximum diameter	124 mm
Length	173.00 mm
Width	124.00 mm
Height	124.00 mm
Outer bulb [PICOS]	G125

## Lifespan

Number of switching cycles	100000
Lifespan	15000 h

## Colors &amp; materials

Product color	Clear
Housing color	Clear

## Temperatures &amp; operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

## Additional product data

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E27

## Capabilities

Dimmable	Yes <sup>1)</sup>
Compatible smart home technology	Amazon Alexa / Google Assistant

<sup>1)</sup> Via App

### Certificates & Standards

Energy efficiency class	F <sup>1)</sup>
Energy consumption	5.00 kWh/1000h
Standards	CE
Type of protection	IP20

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)



### Energy labelling regulation data acc EU 2019/2015


Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	Yes
Color-tuneable light source	Yes
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	≤ 0.5 W
Networked standby power for CLS	≤ 0.5 W
Claim of equivalent power	Yes
Chromaticity coordinate x	0.463
Chromaticity coordinate y	0.420
R9 Colour rendering index	0.00
Beam angle correspondence	SPHERE_360
Survival factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	1254723
Model number	AC42288

### Safety advice

– Do not touch the lamp if broken.

## DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	SH Insert WIFI StartUpG Lamps RGBTW LDV
	Declarations of conformity	SMART WIFI A40 / E40 / G40

Photometric and lighting design files		Document name
	Spectral power distribution	EPREL Data Spectral Diagram LEDr AC42286 AC42287 AC42288 RGBTW

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075777897	Folding box 1	143 mm x 140 mm x 195 mm	188.00 g	3.90 dm <sup>3</sup>
4058075777903	Shipping box 4	304 mm x 290 mm x 207 mm	1018.00 g	18.25 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

– Further information and frequently asked questions (FAQs) at [www.ledvance.com/consumer/smart/faq](http://www.ledvance.com/consumer/smart/faq)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.