

PRODUCT DATASHEET LED TUBE T8 UNIVERSAL PERFORMANCE 600 mm 7.5W 830

LED TUBE T8 UNIVERSAL PERFORMANCE | LED tubes for electronic control gear (ECG), electromagnetic control gear (CCG) and AC mains, shatterproof



Areas of application

- General illumination within ambient temperatures from -20...+45 $^{\circ}\text{C}$
- Illumination of production areas
- Traffic zones and corridors
- Supermarkets and department stores
- Industry

Product benefits

- No bending thanks to glass technology
- Quick, simple and safe replacement without rewiring
- Energy savings of up to 66 % (compared to T8 fluorescent lamp)
- Very high resistance to switching loads
- High luminous flux for sophisticated lighting tasks
- Support the implementation of the HACCP concepts from production through to presentation
- Also suitable for operation at low temperatures

Product features

- LED replacement for classic T8 fluorescent lamps with G13 socket for use in CCG, ECG luminaires or on AC mains
- Compatible with conventional and many common electronic control gears (see also compatibility list) and line voltage
- Low flicker according to EU 2019-2020 (SVM \leq 0.4 / PstLM \leq 1)





- Lamp tube made of glass with splinter protection
- For especially uniform illumination
- Mercury-free and RoHS compliant
- Type of protection: IP20
- Lifetime up to 60,000 h

TECHNICAL DATA


Electrical data

Nominal wattage	7.5 W	
Construction wattage	7.50 W	
Nominal voltage	220240 V	
Operating mode	ECG, CCG, AC Mains 1)	
Nominal current	38 mA	
Type of current	AC	
Inrush current	7 A	
Operating frequency	50/60 Hz	
Mains frequency	50/60 Hz	
Max. lamp number on MCB B10 A	190	
Max. lamp number on MCB B10 A - CCG without compensation	190	
Max. lamp number on MCB B10 A - CCG with compensation	37	
Max. lamp number on MCB B16 A	305	
Max. lamp number on MCB B16 A - CCG without compensation	305	
Max. lamp number on MCB B16 A - CCG with compensation	62	
Total harmonic distortion	< 30 %	
Power factor λ	0.80	

¹⁾ Check ECG compatibility at ledvance.com/compatibility

Photometrical data

Luminous flux	1000 lm
Luminous efficacy	133 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	80
Light color	830
Standard deviation of color matching	≤5 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	≤0.4



EPREL data spectral diagram PROF LEDr 3000K

Light technical data

Beam angle	190 °	
Warm-up time (60 %)	< 0.50 s	
Starting time	< 0.5 s	

Dimensions & Weight



Overall length	603.00 mm
Length with base excl. base pins/connection	600.00 mm
Diameter	27.80 mm
Product weight	153.00 g

Temperatures & operating conditions

Ambient temperature range		-20+45 °C ¹⁾	
	Maximum temperature at tc test point	60 °C	
	Performance temp. acc. to IEC 62717	50 °C ²⁾	

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	60000 h
Lifespan L80/B50 at 25 °C	60000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70

²⁾ In operation with CCG/AC. Tp: 55°C in ECG operation. / Tp rated. Tp point coincides with Tc point - marked on device

	THOUGH DATASH
Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	G13
Mercury content	0.0 mg
Mercury-free	Yes
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	E 1)
Energy consumption	8.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RG0
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G	(lowest efficiency)
Country-specific categorizations	
Order reference	LEDTUBE T8 UN P
LOGISTICAL DATA	
Temperature range at storage	-20+80 °C
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	LED
Non-directional or directional	NDLS

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	603.00 mm

Height	27.80 mm
Width	27.80 mm
Chromaticity coordinate x	0.4339
Chromaticity coordinate y	0.4033
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	°0.9
Displacement factor	0.8
LED light source replaces a fluorescent light source	No
EPREL ID	1317785
Model number	AC42589,AC42589

Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- For operation of LED TUBE T8 UN with a conventional control gear, the existing starter must be exchanged with the including LED starter in the LED tube packaging.
- All electrical connections must be made by a qualified person.
- Not suitable for emergency lighting.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	LEDTUBE T8 UNIVERSAL Ledvance	
PDF	Extended installation guide	Installation instructions LED TUBE T8, T5 und DULUX LED 2024 10 EN	
PDF	Extended installation guide	Notes on the operation of LEDVANCE LED tubes in compensated luminaires	
PDF	Extended installation guide	LEDVANCE Luminaire conversion checklist	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Declarations of conformity	LED TUBES T8 HF/UN	
PDF	Declarations of conformity UKCA	LED TUBES T8 HF/UN UKCA	


	Documents and certificates	Document name	
POF	ECG compatibility list	Ballast compatibility LEDVANCE LED TUBE T5 HF_T8 HF_T8 UNIVERSAL 2025	
	Photometric and lighting design file	es Document name	
	IES file (IES)	LEDTUBE T8 UN P 600 7.5W 830 LEDV	
	LDT file (Eulumdat)	LEDTUBE T8 UN P 600 7.5W 830 LEDV	
	UGR file (UGR table)	LEDTUBE T8 UN P 600 7.5W 830 LEDV	
	Light distribution curve type polar	LEDTUBE T8 UN P 600 7.5W 830 LEDV	
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 3000K	
	Tender texts	Document name	
	Tender documents	LED TUBE T8 UNIVERSAL P 600 mm 7.5W 830-EN	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854026119	Sleeve 1	695 mm x 29 mm x 29 mm	171.00 g	0.58 dm ³
4099854026126	Shipping box 10	742 mm x 210 mm x 115 mm	2142.00 g	17.92 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

- For current information see www.ledvance.com/ledtube

Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.