

PRODUCT DATASHEET LED TUBE T8 EM CONNECTED 1200 mm 16W 840

LED TUBE T8 EM CONNECTED | LED tube for electromagnetic control gear (CCG) works with Connected Sensors, shatterproof



Areas of application

- General illumination within ambient temperatures from -20...+50 $^{\circ}\text{C}$
- Parking lots, warehouses, production areas
- Industry
- Offices

Product benefits

- No bending thanks to glass technology
- Shatter protection thanks to special PET coating
- Short payback period thanks to low energy consumption and maintenance costs

Product features

- Network protocol: ZigBee 3.0 (2.4 GHz mesh network)
- LED TUBE T8 EM Connected can be only operated with LEDVANCE Connected Sensor





TECHNICAL DATA

Electrical data


Nominal wattage	16 W
Construction wattage	16.00 W
Nominal voltage	220240 V
Operating mode	CCG, AC Mains
Nominal current	73 mA
Type of current	AC
Inrush current	3 A
Suitable for DC input	Yes
Input voltage DC	186260 V ¹⁾
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	95
Max. lamp number on MCB B10 A - CCG without compensation	95
Max. lamp number on MCB B10 A - CCG with compensation	16
Max. lamp number on MCB B16 A	155
Max. lamp number on MCB B16 A - CCG without compensation	155
Max. lamp number on MCB B16 A - CCG with compensation	27
Total harmonic distortion	< 20 %
Power factor λ	0.90

¹⁾ Permitted voltage range

Photometrical data

Luminous flux	2400 lm
	150 lm/W
Luminous efficacy	150 111/77
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤5 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1

Stroboscope effect metric (SVM)	0.4
---------------------------------	-----



EPREL data spectral diagram PROF LEDr 4000K

Light technical data

Beam angle	190 °
Warm-up time (60 %)	< 2.00 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	1213.00 mm
Length with base excl. base pins/connection	1200 mm
Diameter	28.00 mm
Base diameter	28 mm
Product weight	214.00 g

Temperatures & operating conditions

Ambient temperature range	-20+50 °C ¹⁾
Maximum temperature at tc test point	75 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70

Rated lamp survival factor at 6,000 h	≥ 0.90	
additional product data		
Base (standard designation)	G13	
Mercury content	0.0 mg	
Mercury-free	Yes	
Design / version	Frosted	
Nama da 1941 a a		
apabilities		
Dimmable	Yes ¹⁾	
Dimmable	Yes ¹⁾	
Dimmable) Only dimmable with LEDVANCE Connected Sensor	Yes ¹⁾	
Dimmable Only dimmable with LEDVANCE Connected Sensor Certificates & Standards	Yes 1) D 1)	
Dimmable Only dimmable with LEDVANCE Connected Sensor		
Dimmable Only dimmable with LEDVANCE Connected Sensor Certificates & Standards Energy efficiency class	D 1)	
) Only dimmable with LEDVANCE Connected Sensor Certificates & Standards Energy efficiency class Energy consumption	D ¹⁾ 16.00 kWh/1000h	

Order reference

LOGISTICAL DATA	
Temperature range at storage	-20+80 °C

LEDTUBE T8 EM C

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	Yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No

Correlated colour temperature type	SINGLE_VALUE
Standby power	<0.5 W
Claim of equivalent power	No
Length	1213.00 mm
Height	28.00 mm
Width	28.00 mm
Chromaticity coordinate x	0.382
Chromaticity coordinate y	0.,380
R9 Colour rendering index	0.00
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	1399430
Model number	AC46524

Accessories Mandatory

Product image	Product name	EAN
9	CONNECTED SENSOR HB	4058075232983
	CONNECTED SENSOR LB	4058075232969
CONTROL OF THE PROPERTY OF THE	CONNECTED SENSOR REMOTE CONTROL	4058075374034

Safety advice

- Not suitable for operation with electronic control gear.
- $\ \, {\sf Operation}\ in\ {\sf outdoor}\ applications\ in\ {\sf suitable}\ damp-proof\ luminaires\ possible\ according\ to\ data\ sheet\ and\ installation\ instruction.$
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Disconnect mains before installation.
- Not suitable for emergency lighting.

DOWNLOAD DATA

	Documents and certificates		Document name	
PDF	User instruction / safety instructions		LEDTUBE T8 EM CON P	
PDF	Legal information		Informationstext 18 Abs 4 ElektroG	
PDF	Declarations of conformity		LED TUBES T8 EM CON	
PDF	Declarations of conformity UKCA		LED TUBES T8 EM CON	
	Photometric and lighting design files		Document name	
	i notometro and lighting design lifes		LEDTUBE T8 EM CON P 1200 16W 840 LEDV	
	IES file (IES)			
	LDT file (Eulumdat)		LEDTUBE T8 EM CON P 1200 16W 840 LEDV	
	UGR file (UGR table)		LEDTUBE T8 EM CON P 1200 16W 840 LEDV	
	Light distribution curve type cone		LEDTUBE T8 EM CON P 1200 16W 840 LEDV	
	Light distribution curve type polar		LEDTUBE T8 EM CON P 1200 16W 840 LEDV	
	Spectral power distribution		EPREL data spectral diagram PROF LEDr 4000K	
	-	D .		
	Tender texts	Document name		
	Tender documents	LED TUBE T8 EM CONNECTED P 1200 mm 16W 840 -EN		

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075823976	Sleeve 1	1,305 mm x 29 mm x 29 mm	243.00 g	1.10 dm ³
4058075823983	Shipping box 10	1,352 mm x 210 mm x 115 mm	3121.00 g	32.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/ledtube

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.