

# PRODUCT DATASHEET DALI-2 SENSOR LS/PD C CI

DALI-2 SENSOR LS-PD C CI | Sensors for wired IOT Light management systems with DALI-2 technology



#### Areas of application

Corridor

#### Product benefits

- Motion detection range optimized for corridors
- Simple and fast installation via wire springs
- DALI-2 certified
- DALI Bus powered (No mains connection necessary)
- Multiple sensors connectable to the same DALI line
- Shutter included to optimize sensor detection
- Integreatable in light- and building management systems supporting DALI-2 sensors

# **Product features**


- Light and motion sensor for ceiling integration
- Motion detection via passive IR element
- Light sensor operating range: 5...2000 lx (measured at sensor)
- Detection height up to 4 meter
- Function indicator LED

# TECHNICAL DATA

# Electrical data

Nominal wattage	0.10 W
Nominal voltage	16 V
Mains frequency	0 Hz

# Dimensions & Weight



Length	105.00 mm
Mounting hole spacing, length	68.00 mm
Width	105.00 mm
Height	80.50 mm
Diameter	105.00 mm
Product weight	120.00 g

# Colors & materials

Product color Light grey
--------------------------

# Temperatures & operating conditions

Ambient temperature range -2	-20+45 °C
------------------------------	-----------

# Capabilities

Dimmable	No
Dimming interface	DALI-2
Maximum installation height	4 m
Detection area	40 m²
Detection angle	360 °
Type of installation	Ceiling integration
Operating range, light sensor	52000 lx

## Certificates & Standards

Approval marks – approval	CE / UKCA
Protection class	П
Type of protection	IP20

## **EQUIPMENT / ACCESSORIES**

- Optional: Ceiling integration via QBM 220-240 LS/PD CM KIT (IP23)
- Optional: IP54 with Surface mounting KIT

#### **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DALI-2 SENSOR LS/PD
PDF	Declarations of conformity	DALI-2 SENSOR LS/PD
PDF	Declarations of conformity UKCA	DALI-2 SENSOR LS/PD
PDF	EU Data Act	Connected Products and Related Software and Services

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899630451	Folding box 1	123 mm x 123 mm x 95 mm	230.00 g	1.44 dm³
4052899630505	Shipping box 24	525 mm x 390 mm x 215 mm	6340.00 g	44.02 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.