

# PRODUCT DATASHEET LED CCT SELECTABLE STICK 9 W/3000 K / 4500 K / 6500 K B22 DIM

LED PERFORMANCE STICK TRI CCT | LED lamps with classic stick shape and TruWave



#### Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

#### Product benefits

- TRI Colour 3000K/4500K/6500K
- LED lamps with innovative TruWave Technology™
- Support sleep/wake cycle thanks mimic of the natural light spectrum
- The balanced blue light spectrum can support attention, reaction time and mood
- Low energy consumption

#### **Product features**

- Color rendering index R<sub>a</sub>: ≥ 80
- Lifetime up to 15,000 h
- Mercury-free lamps



## TECHNICAL DATA

## Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	70 W
Nominal current	50 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50

## Photometrical data

Luminous flux	900 lm
Nominal useful luminous flux 90°	900 lm
Luminous efficacy	100 lm/W
Lumen main.fact.at end of nom.life time	0.70
Color temperature	3000 K / 4500 K / 6500 K
Color rendering index Ra	> 80
Light color	830/845/865
Standard deviation of color matching	≤6 sdcm

# Light technical data

Beam angle	170 °
Starting time	< 0.5 s

## Dimensions & Weight

Overall length	106.00 mm
Diameter	40.00 mm
Maximum diameter	40 mm
Product weight	45.00 g

## Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Lifespan	
Number of switching cycles	100000

#### Additional product data

Base (standard designation)	B22
Mercury content	0.0 mg

# Capabilities

#### Certificates & Standards

Type of protection	IP20
Standards	СВ
Photobiological safety group acc. to EN62778	RG1

## Country-specific categorizations

Order reference	LPSTICKD9W/830/
-----------------	-----------------

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22
Length	106.00 mm
Height	40.00 mm
Width	40.00 mm

#### DOWNLOAD DATA

Photometric and lighting design files Document name	
IES file (IES)	LPSTICKD 9W 830845865 240V-3000K
LDT file (Eulumdat)	LPSTICKD 9W 830845865 240V-3000K
Light distribution curve type polar	LPSTICKD 9W 830845865 240V-3000K

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854082184	Folding box 1	42 mm x 42 mm x 113 mm	62.00 g	0.20 dm <sup>3</sup>
4099854082191	Shipping box 10	226 mm x 96 mm x 134 mm	678.00 g	2.91 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.