# PRODUCT DATASHEET
# Vintage 1906 PenduLum Bell Black

Vintage 1906 PenduLum Bell | Indoor pendant luminaires, vintage style, E27 socket

## Areas of application

– Living areas (living rooms, dining rooms, bedrooms etc.)
– Professional (hotels, bars, boutiques etc.)

## Product benefits

– Individual light scenarios through combination with decorative lamp

## Product features

– Modern minimalistic design
– Made of classic materials
– Special vintage appeal when combined with 1906 lamps
– Flexible mounting options
– Available in various colors

## TECHNICAL DATA

### Electrical data

| | |
|---|---|
| Nominal voltage | 220…240 V |
| Mains frequency | 50…60 Hz |
| Protection class | II |
| Operating mode | Mains voltage |

### Dimensions & Weight

| | |
|---|---|
| Diameter | 92.00 mm |
| Height | 1175.00 mm |
| Product weight | 137.00 g |
| Cable length | 1 m |

1906 PENDULUM BELL E27

### Materials & Colors

| | |
|---|---|
| Product color | Black |
| Housing color | Black |
| Body material | Polyprophylene (PP)|silicone |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

### Application & Mounting

| | |
|---|---|
| Ambient temperature range | -20…+40 °C |
| Temperature range at storage | -20…+80 °C |
| Type of connection | Screw terminal, 2-Pole (L,N) |
| Type of protection | IP20 |
| Dimmable | No |
| Mounting type | Suspended |
| Application environment | Indoor |
| Adjustable | Yes |
| With light source | No |
| Replaceable light source | No |

| | |
|---|---|
| Holder designation | E27 |

## Certificates & Standards

| | |
|---|---|
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |

## Additional product data

| | |
|---|---|
| Product remark | Maximum bulb wattage: 15 W (LED) |
| Number of illuminants | 1 |

## EQUIPMENT / ACCESSORIES

– 1 m connection cable included

## Safety advice

– All electrical connections must be made by a qualified person.
– Caution, risk of electric shock.
– Check wall-ceiling for suitability. If uncertain, seek professional advice.

## DOWNLOAD DATA

| | Documents and certificates | Document name |
|---|---|---|
| PDF | User instruction / safety instructions | UI 1906 PENDULUM BELL |
| PDF | Legal information | Legal Insert PENDULUM |
| PDF | Declarations of conformity | CE Declaration 1906 |
| PDF | Declarations of conformity UKCA | PENDULUM |

## LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---|---|---|---|---|
| 4099854092664 | Folding box 1 | 120 mm x 120 mm x 140 mm | 196.00 g | 2.02 dm³ |
| 4099854092671 | Shipping box 4 | 260 mm x 260 mm x 165 mm | 1131.00 g | 11.15 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

– Further information at www.ledvance.com/consumer/products/product-stories/vintage-edition-1906

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.