

PRODUCT DATASHEET Bathroom Ceiling 310mm E27 Chrome

Bathroom Ceiling Luminaire IP44 E27 | Luminaire with socketed base and IP44



Areas of application

- Indoor applications
- Bathrooms (IP44)

Product benefits

- Socketed luminaire, the lamps can be replaced

Product features

- Type of protection: IP44
- The cover is made of high quality glass



TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	1
Operating mode	Mains voltage

Dimensions & Weight

Diameter	310.00 mm
Height	80.00 mm
Product weight	1300.00 g

BATH CLASSIC ROUND 31CM IP44 E27

Materials & Colors

Product color	Chrome
Housing color	Chrome
Body material	Steel
Cover material	Glass
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Screw terminal, 3-Pole
Type of protection	IP44
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	No
Replaceable light source	No

Holder designation	E27
--------------------	-----

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data

Product remark	Maximum bulb wattage: 15 W (LED)
Number of illuminants	1

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	UI BATHROOM CLASSIC ROUND
POF	Legal information	Legal Insert
POF	Declarations of conformity	CE Declaration Bathroom Classic
POF	Declarations of conformity UKCA	UKCA Declaration Bathroom Classic

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854103353	Folding box 1	110 mm x 340 mm x 340 mm	1764.00 g	12.72 dm ³
4099854103360	Shipping box 4	470 mm x 350 mm x 370 mm	7790.00 g	60.87 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

⁻ Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.