

PRODUCT DATASHEET LED PERFORMANCE STICK 11 W/6500 K E27 DIM

LED PERFORMANCE STICK | LED lamps, classic stick shape



Areas of application

- Suitable for indoor applications.
- $\,$ Replacement for conventional compact fluorescent lamps with wattage 11 W, 15 W and 24 W

Product benefits

- Creation of the preferred light ambience thanks to dimming
- Wide beam angle: 200°
- Instant 100 % light, no warm-up time
- Stylish and modern design
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

Product features

- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Long lifetime up to 25,000 h
- Mercury-free lamps
- Input voltage: 220...240 V_{AC}
- Storage temperature from -20 °C to up to +80 °C, up to 95 % relative humidity



– Operating temperature from -20 $^{\circ}\text{C}$ to up to +35 $^{\circ}\text{C}$, up to 95 % relative humidity

TECHNICAL DATA

Electrical data

Nominal wattage	11 W
Construction wattage	11.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	55 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.70

Photometrical data

Luminous flux	1050 lm
Nominal useful luminous flux 90°	1050 lm
Luminous efficacy	95 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	200 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	121.00 mm
Diameter	46.00 mm
Maximum diameter	46 mm
Product weight	35.00 g

Temperatures & operating conditions

|--|

Lifespan

Number of switching cycles	100000
Additional product data	
Base (standard designation)	E27
Mercury content	0.0 mg

Capabilities

Dimmable	Yes

Certificates & Standards

Type of protection	IP20
Standards	CB / SAA

Country-specific categorizations

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	121.00 mm
Height	46.00 mm
Width	46.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075731950	Folding box 1	47 mm x 47 mm x 121 mm	48.00 g	0.27 dm ³
4058075731967	Shipping box 10	246 mm x 103 mm x 138 mm	577.00 g	3.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.