

PRODUCT DATASHEET LED GLOBE 9W 6500k BIVFR E27

CLASSIC G (GLOBO) | LED bulb with globe format, base E27



Areas of application

- All domestic rooms, especially where the lamps are visible
- For indoor use only
- General illumination
- Domestic applications
- Decorative applications

Product benefits

- Instant 100 % light, no warm-up time
- Low energy consumption
- Three year guarantee

Product features

- Lifetime up to 15,000 h
- Mercury-free and RoHS compliant
- Uniform illumination
- Type of protection: IP20
- Base: E27



TECHNICAL DATA

Electrical data

Nominal wattage	9 W
Nominal voltage	100240 V
Nominal current	80 mA
Type of current	AC
Power factor λ	≥0.90

Photometrical data

Luminous flux	900 lm
Luminous efficacy	100 lm/W
Light color (designation)	Cool Daylight
Color rendering index Ra	≥ 80
Light color	8

Light technical data

Starting time	< 0.5 s

Dimensions & Weight

Product weight	46.00 g
	9

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	15000

Additional product data

	All technical parameters apply to the entire lamp / Due to the complex	
Product remark	production process for light-emitting diodes, the typical values shown	
	for the technical LED parameters are purely statistical values that do	
	not necessarily match the actual technical parameters of each	
	individual product, which can vary from the typical value	

Capabilities

Certificates & Standards

Type of protection	IP20
Photobiological safety group acc. to EN62778	RG0

Country-specific categorizations

Order reference	LED GLOBE 9W/86		
Energy labelling regulation data acc EU 2019/2015			
Lighting technology used	LED		
Connected light source (CLS)	No		
Color-tuneable light source	No		
Envelope	No		

No

No

No

LOGISTICAL DATA

Anti-glare shield

High luminance light source

Claim of equivalent power

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075783201	Folding box 1	60 mm x 60 mm x 113 mm	51.00 g	0.41 dm ³
4058075783218	Shipping box 12	244 mm x 91 mm x 121 mm	1354.00 g	2.69 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.